



# ALTV615DC48ULCBM UL Listed DC CCTV Power Supply

Rev. DSALTV615DC48ULCBM - 10222012



ALTV615DC48ULCBM

## **Overview**

ALTV615DC48ULCBM provides 6VDC to 15VDC distributed via eight (8) Class 2 Rated PTC protected power limited outputs for powering CCTV Cameras, heaters and other video accessories.

## **Specifications**

### ***Input:***

- Input 115VAC, 50/60 Hz, 0.9 amp.

### ***Output:***

- Eight (8) Class 2 Rated PTC protected power limited outputs.
- 6VDC to 15VDC field adjustable.
- 4 amp total continuous supply current  
(0.5 amp per device, 2.5 amp max.).
- Outputs are rated @ 2.5 amp.
- Filtered and electronically regulated outputs.

### ***Electrical:***

- Operating temperature: 0° C to 49° C ambient.
- 9-23 BTU/Hr.
- System AC input VA requirement: 103.5VA.

### ***Features:***

- AC input and DC output LED indicators.
- Power ON/OFF switch.
- Unit maintains camera synchronization.
- Ease of installation saves time and eliminates costly labor.

### ***Mechanical:***

- NEMA1 enclosure.
- Enclosure Dimensions (H x W x D approx.):  
8.5" (215.9mm) x 7.5" (190.5mm) x 3.75" (95.25mm)
- Product weight (approx.): 8.65 lbs. (3.92 kg.).
- Shipping weight (approx.): 9.15 lbs. (4.15 kg.).

## **Agency Approvals**



UL Listed for Commercial CCTV Equipment  
(UL 2044).



CUL Listed - CSA Standard C22.2 No.1-98,  
Audio, Video and Similar Equipment.

**Enclosure Dimensions (H x W x D) (approximate):**  
 8.5" (215.9mm) x 7.5" (190.5mm) x 3.75" (95.25mm)

