



ALTV615DC4UL

Overview

ALTV615DC4UL is designed with four (4) Class (2) Rated fuse protected power limited outputs for powering CCTV Cameras and other video accessories. It will provide 5.5-15VDC distributed via four (4) outputs with a total of up to 2.5 amp continuous supply current.

Specifications

Input:

- Input 24VAC/40VA or 24VAC/50VA, UL Listed Plug-in transformer.

Output:

- Four (4) Class 2 Rated fuse protected power limited outputs.
- 5.5VDC to 15VDC field adjustable.

Transformer	Output current 5.5VDC to 12VDC	Output current 12VDC to 15VDC
24VAC/40VA	2.25 amp	1.8 amp
24VAC/50VA	2.5 amp	2.5 amp

- Output fuses are rated @ 1.0 amp/250VAC.
- Filtered and electronically regulated outputs.

Electrical:

- Operating temperature: 0° C to 49° C ambient.
- BTU/Hr.

Transformer	5.5VDC to 12VDC	12VDC to 15VDC
24VAC/40VA	6.33-13.82 BTU/Hr.	11.05-13.82 BTU/Hr.
24VAC/50VA	7.04-15.35 BTU/Hr.	15.35-19.19 BTU/Hr.

Electrical (cont'd):

- System AC input VA requirement:
24VAC/40VA: 192.05VA.
24VAC/50VA: 241.5VA.

Features:

- AC input and DC output LED indicators.
- Power ON/OFF switch.
- Spare fuse(s) provided.
- Unit maintains camera synchronization.
- Ease of installation saves time and eliminates costly labor.

Mechanical:

- Enclosure Dimensions (H x W x D approx.):
8.5" (215.9mm) x 7.5" (190.5mm) x 3.5" (88.9mm)
- Product weight (approx.): 3.4 lbs. (1.54 kg.).
- Shipping weight (approx.): 3.9 lbs. (1.77 kg.).

Agency Approvals



UL Listed for Commercial CCTV Equipment (UL 2044).



CUL Listed - CSA Standard C22.2 No.1-98, Audio, Video and Similar Equipment.

Enclosure Dimensions (H x W x D) (approximate):

8.5" (215.9mm) x 7.5" (190.5mm) x 3.5" (88.9mm)

