



ALTV615DC8ULCB3

### **Overview**

ALTV615DC8ULCB3 is designed with eight (8) individually Class 2 Rated PTC protected power limited outputs for powering CCTV Cameras and other video accessories. Factory installed 3-wire line cord.

### **Specifications**

#### ***Input:***

- Input 115VAC, 50/60 Hz, 0.9 amp.

#### ***Output:***

- Eight (8) Class 2 Rated PTC protected power limited outputs.
- 6VDC to 15VDC field adjustable.
- 4 amp total continuous supply current  
(0.50 amp per device, 2.5 amp max.).
- Outputs are rated @ 2.5 amp.
- Filtered and electronically regulated outputs.

#### ***Electrical:***

- Operating temperature: 0° C to 49° C ambient.
- 12.28-30.71 BTU/Hr.
- System AC input VA requirement: 103.5VA.

#### ***Features:***

- AC input and DC output LED indicators.
- Factory installed 3-wire line cord.
- Power ON/OFF switch.
- Unit maintains camera synchronization.
- Ease of installation saves time and eliminates costly labor.

#### ***Mechanical:***

- NEMA1 enclosure.
- Enclosure Dimensions (H x W x D approx.):  
13.5" (342.9mm) x 13" (330.2mm) x 3.25" (82.55mm)
- Product weight (approx.): 11.5 lbs. (5.22 kg.).
- Shipping weight (approx.): 12.0 lbs. (5.44 kg.).

### **Agency Approvals**



UL Listed for Commercial CCTV Equipment  
(UL 2044).



CUL Listed - CSA Standard C22.2 No.1-98,  
Audio, Video and Similar Equipment.

**Enclosure Dimensions (H x W x D) (approximate):**

13.5" (342.9mm) x 13" (330.2mm) x 3.25" (82.55mm)

