



eFlow102N

### **Overview**

eFlow102N is a power supply/charger that converts a 120VAC, 60Hz input into a single 12VDC Class 2 Rated output.



### **Specifications**

#### **Input:**

- 120VAC, 60Hz, 3.5 amp.
- Input fuse: 5A/250V.

#### **Output:**

- 12VDC @ 10.0 amp supply current.
- Class 2 Rated output.
- Auxiliary Power-Limited output rated @ 1 amp (unswitched).
- Over Voltage Protection.

#### **Battery Backup:**

- Built-in charger for sealed lead acid or gel type batteries.
- Maximum charge current 1.54 amp.
- Automatic switch over to stand-by battery when AC fails. Transfer to stand-by battery power is instantaneous with no interruption.

#### **Supervision:**

- AC fail supervision (form “C” contacts).
- Battery fail & presence supervision (form “C” contacts).
- Low power shutdown. Shuts down DC output terminals if battery voltage drops below 71-73% for 12V units and 70-75% for 24V units (depending on the power supply). Prevents deep battery discharge.

#### **Fire Alarm Disconnect:**

- Supervised Fire Alarm disconnect (latching or non-latching) 10K EOL resistor. Operates on a normally open (NO) or normally closed (NC) trigger.

#### **Electrical:**

- Operating temperature: 0° C to 49° C ambient.
- BTU/Hr.: 61.42 BTU/Hr.
- System AC input VA requirement: 420VA.

#### **Visual Indicators:**

- Green AC Power LED indicates 120VAC present.
- AC input, DC output and Battery LED indicators.

#### **Additional Features:**

- Short circuit and overload protection.
- Unit is complete with power supply, enclosure, battery leads and cam lock.

#### **Mechanical:**

- Enclosure Dimensions (H x W x D approx.): 13.5” (342.9mm) x 13” (330.2mm) x 3.25” (82.55mm) - Accommodates up to two (2)12VDC/7AH batteries.
- Product weight (approx.): 8.5 lbs. (3.86 kg).
- Shipping weight (approx.): 9.4 lbs. (4.26 kg).

### **Agency Approvals**



- UL 294 UL Listed for Access Control System Units.
- UL 603 UL Listed for Power Supplies for Use with Burglar-Alarms Systems.
- UL 1481 UL Listed for Power Supplies for Fire Protective Signaling Systems.



- ULC-S318-96 - Power Supplies for Burglar Alarm Systems. Also suitable for Access Control.



- CSFM - California State Fire Marshal Approved.

**Enclosure Dimensions (H x W x D) (approximate):**

13.5" (342.9mm) x 13" (330.2mm) x 3.25" (82.55mm)

