



OLS75

Overview

OLS75 power supply/charger converts a 115VAC, 50/60Hz or 230VAC, 50/60Hz input into a 12VDC or 24VDC output @ 2.5 amp continuous supply current (*see specifications*). This unit has a wide range of applications for access control and security system accessories that require additional power.

Specifications

Input:

- Universal input 115VAC, 50/60Hz, 0.95 amp or 230VAC, 50/60Hz, 0.6 amp.

Output:

- 12VDC or 24VDC selectable output.
- 2.5 amp continuous supply current.
- Filtered and electronically regulated output.
- Short circuit and thermal overload protection.

Battery Backup:

- Built-in charger for sealed lead acid or gel type batteries.
- Automatic switch over to stand-by battery when AC fails.
- Maximum charge current 0.5 amp.

Supervision:

- AC fail supervision (form "C" contacts).
- Low battery supervision (form "C" contacts).

Visual Indicators:

- AC input and DC output LED indicators.

Electrical:

- Operating temperature: -20°C to 49°C ambient.
- BTU/Hr.:
 - 12VDC: 15.35 BTU/Hr.
 - 24VDC: 30.7 BTU/Hr.
- System AC input VA requirement:
 - 115VAC: 109.25VA.
 - 230VAC: 138VA.

Features:

- Power ON/OFF switch.
- Includes battery leads.

Mechanical:

- Product weight (approx.): 1.55 lbs. (0.70 kg).
- Shipping weight (approx.): 1.75 lbs. (0.79 kg).

Board Dimensions (L x W x H approximate):

7.24" x 4.508" x 1.75" (183.9mm x 114.52mm x 44.45mm)

