



# R248600CB AC Rack Mount CCTV Power Supply

Rev. DSR248600CB\_10252012



R248600CB

## **Overview**

R248600CB provides 24VAC or 28VAC distributed via eight (8) PTC protected outputs for powering CCTV Cameras, heaters and other video accessories.

## **Specifications**

### ***Input:***

- 115VAC, 50/60Hz, 6 amp.

### ***Output:***

- Eight (8) PTC protected outputs.
- 24VAC @ 28 amp (672VA) supply current (3.5 amp per device, 2.5 amp max.)
- or 28VAC @ 25 amp (700VA) supply current (3.125 amp per device, 2.5 amp max.).
- Outputs are rated @ 2.5 amp.
- Surge suppression.

### ***Electrical:***

- Operating temperature: 0° C to 49° C ambient.
- 343.94 or 358.27 BTU/Hr.
- System AC input VA requirement: 690VA.

### ***Features:***

- Eight (8) power LEDs.
- Illuminated master power disconnect circuit breaker with manual reset.
- 3-wire grounded line cord.
- Removable terminal blocks with locking screw flange.
- Spare fuses provided.

### ***Mechanical:***

- 2U rack mount chassis for use in standard EIA 19" rack.
- Enclosure Dimensions (H x W x D approx.): 3.26" (83mm) x 19.125" (486mm) x 8.5" (216mm)
- Product weight (approx.): 23 lbs. (10.43 kg).
- Shipping weight (approx.): 24 lbs. (10.89 kg).

**Enclosure Dimensions (H x W x D) (approximate):**  
 3.26" (83mm) x 19.125" (486mm) x 8.5" (216mm)

