



R248ULi Isolated Rack Mount CCTV Power Supply

Rev. DSR248ULi_10252012



R248ULi

Overview

R248ULi provides 24VAC distributed via eight (8) isolated fuse protected outputs for powering CCTV Cameras, heaters and other video accessories.

Specifications

Input:

- 115VAC, 50/60Hz, 2.7 amp.

Output:

- Eight (8) isolated fuse protected outputs.
- 24VAC @ 12.5 amp (300VA) supply current (1.56 amp per device, 3.5 amp max.)
- Outputs are rated @ 3.5 amp.
- Surge suppression.

Electrical:

- Operating temperature: 0° C to 49° C ambient.
- 114 BTU/Hr.
- System AC input VA requirement: 310.5VA.

Features:

- Eight (8) power LEDs.
- Illuminated master power disconnect circuit breaker with manual reset.
- 3-wire grounded line cord.
- Removable terminal blocks with locking screw flange.
- Spare fuses provided.

Mechanical:

- 2U rack mount chassis for use in standard EIA 19" rack.
- Enclosure Dimensions (H x W x D approx.): 3.26" (83mm) x 19.125" (486mm) x 8.5" (216mm)
- Product weight (approx.): 17.2 lbs. (7.80 kg).
- Shipping weight (approx.): 18.2 lbs. (8.26 kg).

Agency Approvals



UL Listed for Commercial CCTV Equipment (UL 2044).



CUL Listed - CSA Standard C22.2 No.1-98, Audio, Video and Similar Equipment.



European Conformity

Enclosure Dimensions (H x W x D) (approximate):
 3.26" (83mm) x 19.125" (486mm) x 8.5" (216mm)

