



VertiLine33TD

VERTILINE

Overview

Vertiline33TD Rack Mount DC Power Supply provides sixteen (16) filtered and electronically regulated power outputs in a space saving 1U EIA 19" rack mount chassis. Vertiline Rack Mount Power Supplies are also available in 24VDC and eight (8) outputs configurations.

Specifications

Input:

- 115VAC 60 Hz, 3 amp input.

Output:

- 12VDC outputs rated @ 16 amp total current max. (1.0 amp per device, 2.5 amp max.).
- Sixteen (16) PTC protected power outputs.
- Filtered and electronically regulated.

Electrical:

- Operating temperature: -20° C to 49° C ambient.
- 98.27 BTU/Hr.
- System AC input VA requirement: 345VA.

Features:

- Sixteen (16) power LEDs.

Features (cont'd):

- Illuminated master power disconnect circuit breaker with manual reset.
- IEC 320 - 3-wire grounded line cord (detachable).
- Removable terminal blocks with locking screw flange.

Mechanical:

- Units can be rack, wall or shelf mounted.
- Modular 1U standard EIA 19" rack mount chassis.
- Enclosure Dimensions (H x W x D approx.): 1.625" (41.275mm) x 19.125" (486mm) x 8.5" (216mm).
- Product weight (approx.): 7.95 lbs. (3.61 kg).
- Shipping weight (approx.): 9.05 lbs. (4.11 kg).

Agency Approvals



European Conformity

Enclosure Dimensions (H x W x D) (approximate):
1.625" (41.275mm) x 19.125" (486mm) x 8.5" (216mm)

