



WPTV248300ULCB UL Listed AC Outdoor CCTV Power Supply

Rev. DSWPTV248300ULCB - 03012013



WPTV248300ULCB

Overview

WPTV248300ULCB outdoor CCTV Power Supply provides power via eight (8) PTC protected Class 2 rated power-limited outputs for CCTV Cameras, heaters and other video accessories.

Specifications

Input:

- 115VAC, 50/60Hz, 1.76 amp.

Output:

- Eight (8) PTC protected outputs.
- 24VAC @ 12.5 amp (300VA) supply current.
- or 28VAC @ 6.25 amp (175VA) supply current.
- Outputs are rated @ 2.5 amp.
- Surge suppression.

Electrical:

- Operating temperature: 0° C to 49° C ambient.
- BTU/Hr.: 153.55 BTU/Hr.
- System AC input VA requirement: 202.4VA.

Features:

- Secondary fuse rated @ 5 amp/250V.
- Unit maintains camera synchronization.
- AC power LED.
- Power ON/OFF switch.
- Spare fuses provided.
- (all models w/primary and/or secondary fuses).
- NEMA 4 Rated enclosure for outdoor use.

Mechanical:

- Enclosure Dimensions (H x W x D approx.): 12" (304.8mm) x 8" (203.2mm) x 6" (152.4mm).
- Product weight (approx.): 14.4 Lbs (6.53 kg).
- Shipping weight (approx.): 16.4 Lbs (7.44 kg).

Agency Approvals



UL Listed for Commercial CCTV Equipment (UL 2044).



CUL Listed - CSA Standard C22.2 No.1-98, Audio, Video and Similar Equipment.



European Conformity



PMK1

PMK1 Pole Mount Kit (order separately)

PMK1 pole mount kit is designed to simplify installation of outdoor units.

- Accommodates 2"- 8"(diameter) poles.
- Kit includes:
 - Two (2) powder coated steel mount brackets.
 - Four (4) stainless steel bolts.
 - Four (4) stainless steel lock washers.
 - Two (2) wormgear quick release straps.

Enclosure Dimensions (H x W x D) (approximate):

12" (304.8mm) x 8" (203.2mm) x 6" (152.4mm)

