

# HER151 - HER158

**PRV : 50 - 1000 Volts**  
**Io : 1.5 Amperes**


## FEATURES :

- \* High current capability
- \* High surge current capability
- \* High reliability
- \* Low reverse current
- \* Low forward voltage drop
- \* Fast switching for high efficiency

## MECHANICAL DATA :

- \* Case : DO-41 Molded plastic
- \* Epoxy : UL94V-O rate flame retardant
- \* Lead : Axial lead solderable per MIL-STD-202, Method 208 guaranteed
- \* Polarity : Color band denotes cathode end
- \* Mounting position : Any
- \* Weight : 0.34 gram

## HIGH EFFICIENT RECTIFIER DIODES



## MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Rating at 25 °C ambient temperature unless otherwise specified.  
 Single phase, half wave, 60 Hz, resistive or inductive load.  
 For capacitive load, derate current by 20%.


| RATING  | SYMBOL | HER 151       | HER 152 | HER 153 | HER 154 | HER 155 | HER 156 | HER 157 | HER 158 | UNIT |    |
|---|--------|---------------|---------|---------|---------|---------|---------|---------|---------|------|----|
| Maximum Recurrent Peak Reverse Voltage  | VRRM   | 50            | 100     | 200     | 300     | 400     | 600     | 800     | 1000    | V    |    |
| Maximum RMS Voltage   | VRMS   | 35            | 70      | 140     | 210     | 280     | 420     | 560     | 700     | V    |    |
| Maximum DC Blocking Voltage   | VDC    | 50            | 100     | 200     | 300     | 400     | 600     | 800     | 1000    | V    |    |
| Maximum Average Forward Current<br>0.375"(9.5mm) Lead Length Ta = 55 °C   | IF(AV) | 1.5           |         |         |         |         |         |         |         | A    |    |
| Maximum Peak Forward Surge Current,<br>8.3ms Single half sine wave superimposed<br>on rated load (JEDEC Method) | IFSM   | 60            |         |         |         |         |         |         |         | A    |    |
| Maximum Forward Voltage at IF = 1.5 A   | VF     | 1.1           |         |         |         |         | 1.7     |         |         |      | V  |
| Maximum DC Reverse Current Ta = 25 °C<br>at Rated DC Blocking Voltage Ta = 100 °C                               | IR     | 5             |         |         |         |         |         |         |         | µA   |    |
|   | IR(H)  | 50            |         |         |         |         |         |         |         | µA   |    |
| Maximum Reverse Recovery Time ( Note 1 )  | Trr    | 50            |         |         |         |         | 75      |         |         |      | ns |
| Typical Junction Capacitance ( Note 2 )   | CJ     | 50            |         |         |         |         |         |         |         | pf   |    |
| Junction Temperature Range  | TJ     | - 65 to + 150 |         |         |         |         |         |         |         | °C   |    |
| Storage Temperature Range   | TSTG   | - 65 to + 150 |         |         |         |         |         |         |         | °C   |    |

### Notes :


- ( 1 ) Reverse Recovery Test Conditions : IF = 0.5 A, IR = 1.0 A, Irr = 0.25 A.
- ( 2 ) Measured at 1.0 MHz and applied reverse voltage of 4.0 Vdc

## RATING AND CHARACTERISTIC CURVES ( HER151 - HER158 )


**FIG.1 - REVERSE RECOVERY TIME CHARACTERISTIC AND TEST CIRCUIT DIAGRAM**




**FIG.2 - DERATING CURVE FOR OUTPUT RECTIFIED CURRENT**



**FIG.3 - MAXIMUM NON-REPETITIVE PEAK FORWARD SURGE CURRENT**



**FIG.4 - TYPICAL FORWARD CHARACTERISTICS**



**FIG.5 - TYPICAL REVERSE CHARACTERISTICS**

