

M·C·C·

Micro Commercial Components



Micro Commercial Components
20736 Marilla Street Chatsworth
CA 91311
Phone: (818) 701-4933
Fax: (818) 701-4939

**SB220
Thru
SB260**

Features

- Lead Free Finish/Rohs Compliant (Note1) ("P" Suffix designates Compliant. See ordering information)
- Schottky Barrier Rectifier
- Guard Ring Protection
- High Surge Current Capability
- Epoxy meets UL 94 V-0 flammability rating
- Moisture Sensitivity Level 1
- For Use in Low Voltage, High Frequency Inverters, Free Wheeling, and Polarity Protection Applications
- Halogen free available upon request by adding suffix "-HF"

Maximum Ratings

- Operating Temperature: -65°C to +150°C
- Storage Temperature: -65°C to +150°C
- Maximum Thermal Resistance: 15K/W Junction To Lead
50K/W Junction to Ambient*

MCC Part Number	Maximum Recurrent Peak Reverse Voltage	Maximum RMS Voltage	Maximum DC Blocking Voltage
SB220	20V	14V	20V
SB230	30V	21V	30V
SB240	40V	28V	40V
SB245	45V	31.5V	45V
SB250	50V	35V	50V
SB260	60V	42V	60V

Electrical Characteristics @ 25°C Unless Otherwise Specified


Average Rectified Output current*	I_o	2A	$T_L = 100^\circ\text{C}$
Maximum surge current	I_{FSM}	50A	8.3ms, half sine
Max peak forward voltage SB220-SB245 SB250-SB260	V_{FM}	.50V .70V	$I_{FM} = 2.0\text{A}$
Max peak reverse current	I_{RM}	0.5mA 10mA	$T_A = 25^\circ\text{C}$ $T_A = 100^\circ\text{C}$
Typical junction capacitance SB220-SB245 SB250-SB260	C_J	170pF 140pF	$V_R = 4.0\text{V}$, $f=1.0\text{MHz}$

*Valid provided that leads are kept at ambient temperature at a distance of 915mm from the case






Note: 1. High Temperature Solder Exemptions Applied, see EU Directive Annex 7.

**2 Amp Schottky Rectifier
20V-60V**

DO-15



DIMENSIONS					
DIM.	INCHES		MM		NOTE
	MIN	MAX	MIN	MAX	
A	.230	.300	5.80	7.60	
B	.104	.140	2.60	3.60	
C	.026	.034	.70	.90	
D	1.000	---	25.40	---	



Ordering Information :

Device	Packing
Part Number-TP	Tape&Reel: 4Kpcs/Reel
Part Number-AP	Ammo Packing: 3Kpcs/Ammo Box
Part Number-BP	Bulk: 25Kpcs/Carton

Note : Adding "-HF" suffix for halogen free, eg. Part Number-TP-HF

IMPORTANT NOTICE

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications , enhancements , improvements , or other changes . **Micro Commercial Components Corp.** does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights ,nor the rights of others . The user of products in such applications shall assume all risks of such use and will agree to hold **Micro Commercial Components Corp.** and all the companies whose products are represented on our website, harmless against all damages.

LIFE SUPPORT

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

CUSTOMER AWARENESS

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. **MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources.** MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.