

**M·C·C**

Micro Commercial Components



Micro Commercial Components  
20736 Marilla Street Chatsworth  
CA 91311  
Phone: (818) 701-4933  
Fax: (818) 701-4939

**BCW68H****Features**

- Lead Free Finish/RoHS Compliant ("P" Suffix designates RoHS Compliant. See ordering information)
- Ideally Suited for Automatic Insertion
- 150°C Junction Temperature
- Low Current, Low Frequency
- Epitaxial Planar Die Construction
- Epoxy meets UL 94 V-0 flammability rating
- Moisture Sensitivity Level 1
- Halogen free available upon request by adding suffix "-HF"

**Mechanical Data**

- Case: SOT-23, Molded Plastic
- Terminals: Solderable per MIL-STD-202, Method 208
- Marking: DH
- Weight: 0.008 grams (approx.)


**Maximum Ratings @ 25°C Unless Otherwise Specified**

Characteristic	Symbol	Value	Unit
Collector-Emitter Voltage	$V_{CEO}$	-45	V
Collector-Base Voltage	$V_{CBO}$	-60	V
Emitter-Base Voltage	$V_{EBO}$	-5	V
Collector Current(DC)	$I_C$	-800	mA
Peak Collector Current	$I_{CM}$	-1000	mA
Base Current(DC)	$I_B$	-100	mA
Peak Base Current	$I_{BM}$	-200	mA
Power Dissipation@ $T_s=79^\circ\text{C}$	$P_d$	330	mW
Thermal Resistance, Junction to Ambient Air	$R_{\theta JA}$	285 <sup>(1)</sup>	°C/W
Thermal Resistance, Junction to Soldering Point	$R_{\theta JS}$	215	°C/W
Operating & Storage Temperature	$T_j, T_{STG}$	-55~150	°C


**Notes:**

(1) Valid provided that leads are kept at ambient temperature.

**PNP Small**  
**Signal Transistor**  
**330mW**



DIM	INCHES		MM		NOTE
	MIN	MAX	MIN	MAX	
A	.110	.120	2.80	3.04	
B	.083	.104	2.10	2.64	
C	.047	.055	1.20	1.40	
D	.035	.041	.89	1.03	
E	.070	.081	1.78	2.05	
F	.018	.024	.45	.60	
G	.0005	.0039	.013	.100	
H	.035	.044	.89	1.12	
J	.003	.007	.085	.180	
K	.015	.020	.37	.51	

**Suggested Solder Pad Layout****www.mccsemi.com**

**Electrical Characteristics** (TA = 25°C unless otherwise noted)

	Symbol	Min.	TYP.	Max.	Unit
DC Current Gain <sup>(1)</sup> at V <sub>CE</sub> = 1V, I <sub>C</sub> = 10mA at V <sub>CE</sub> = 2V, I <sub>C</sub> = 100mA at V <sub>CE</sub> = 2V, I <sub>C</sub> = 500mA	h <sub>FE</sub> h <sub>FE</sub> h <sub>FE</sub>	180 250 100		630	
Collector-Emitter Saturation Voltage <sup>(1)</sup> at I <sub>C</sub> = 100mA, I <sub>B</sub> = 10mA at I <sub>C</sub> = 500mA, I <sub>B</sub> = 50mA	V <sub>CEsat</sub> V <sub>CEsat</sub>	— —	— —	0.3 1.0	V V
Base-Emitter Saturation Voltage <sup>(1)</sup> at I <sub>C</sub> = 100mA, I <sub>B</sub> = 10mA at I <sub>C</sub> = 500mA, I <sub>B</sub> = 50mA	V <sub>BEsat</sub> V <sub>BEsat</sub>	— —	— —	1.25 2	V V
Collector-Emitter Breakdown Voltage at I <sub>C</sub> = 10mA, I <sub>B</sub> = 0	V <sub>(BR)CEO</sub>	45	—	—	V
Collector-Base Breakdown Voltage at I <sub>C</sub> = 10μA, I <sub>B</sub> = 0	V <sub>(BR)CBO</sub>	60	—	—	V
Emitter-Base Breakdown Voltage at I <sub>E</sub> = 10μA, at I <sub>C</sub> = 0	V <sub>(BR)EBO</sub>	5	—	—	V
Collector-Base Cut-off Current at V <sub>CB</sub> = 45V, I <sub>E</sub> = 0 at V <sub>CB</sub> = 45V, I <sub>E</sub> = 0, TA = 150°C	I <sub>CBO</sub> I <sub>CBO</sub>	— —	— —	20 20	nA μA
Emitter-Base Cut-off Current at V <sub>EB</sub> = 4V, I <sub>C</sub> = 0	I <sub>EBO</sub>	—	—	20	nA
Gain-Bandwidth Product at V <sub>CE</sub> = 10V, I <sub>C</sub> = 20mA, f = 100MHz	f <sub>T</sub>	—	100	—	MHz
Collector-Base Capacitance at V <sub>CB</sub> = 10V, f = 1MHz	C <sub>CB</sub>	—	6	—	pF
Emitter-Base Capacitance at V <sub>EB</sub> = 0.5V, f = 1MHz	C <sub>EB</sub>	—	60	—	pF

**Note:** (1) Pulse test: t ≤ 300μs, D = 2%

## Ordering Information :

Device	Packing
Part Number-TP	Tape & Reel; 3 Kpcs/ Reel

Note : Adding "-HF" suffix for halogen free, eg. Part Number-TP-HF

### \*\*\*IMPORTANT NOTICE\*\*\*

**Micro Commercial Components Corp.** reserves the right to make changes without further notice to any product herein to make corrections, modifications , enhancements , improvements , or other changes . **Micro Commercial Components Corp.** does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights ,nor the rights of others . The user of products in such applications shall assume all risks of such use and will agree to hold **Micro Commercial Components Corp.** and all the companies whose products are represented on our website, harmless against all damages.

### \*\*\*LIFE SUPPORT\*\*\*

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

### \*\*\*CUSTOMER AWARENESS\*\*\*

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. **MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources.** MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.