



Micro Commercial Components

Micro Commercial Components
 20736 Marilla Street Chatsworth
 CA 91311
 Phone: (818) 701-4933
 Fax: (818) 701-4939

MMDT4403

PNP Plastic-Encapsulate Transistors

Features

- Halogen free available upon request by adding suffix "-HF"
- Lead Free Finish/RoHS Compliant ("P" Suffix designates RoHS Compliant. See ordering information)
- Epitaxial Planar Die Construction
- Ideal for Low Power Amplification and Switching
- Epoxy meets UL 94 V-0 flammability rating
- Moisture Sensitivity Level 1
- Marking: K4M/K2T


Maximum Ratings @ 25°C Unless Otherwise Specified

Symbol	Rating	Rating(PNP)	Unit
V_{CE0}	Collector-Emitter Voltage	40	V
V_{CBO}	Collector-Base Voltage	40	V
V_{EBO}	Emitter-Base Voltage	5	V
I_C	Collector Current-Continuous	0.6	A
P_C	Collector Dissipation	0.2	W
T_J	Operating Junction Temperature	-55 to +150	°C
T_{STG}	Storage Temperature	-55 to +150	°C


Electrical Characteristics @ 25°C Unless Otherwise Specified

Symbol	Parameter	Min	Max	Units	
$V_{(BR)CEO}$	Collector-Emitter Breakdown Voltage ($I_C=-1mA_{dc}, I_B=0$)	40	---	Vdc	
$V_{(BR)CBO}$	Collector-Base Breakdown Voltage ($I_C=100\mu A_{dc}, I_E=0$)	40	---	Vdc	
$V_{(BR)EBO}$	Collector-Emitter Breakdown Voltage ($I_E=100\mu A_{dc}, I_C=0$)	5	---	Vdc	
I_{CBO}	Collector Cutoff Current ($V_{CB}=50V_{dc}, I_E=0$)	---	0.1	μA_{dc}	
I_{EBO}	Emitter Cutoff Current ($V_{EB}=-5V_{dc}, I_C=0$)	---	0.1	μA_{dc}	
h_{FE}	DC Current Gain ($I_C=0.1mA_{dc}, V_{CE}=1V_{dc}$)	30	---	---	
	($I_C=1mA_{dc}, V_{CE}=1V_{dc}$)	60	---		
	($I_C=10mA_{dc}, V_{CE}=1V_{dc}$)	100	---		
	($I_C=150mA_{dc}, V_{CE}=2V_{dc}$)	100	300		
	($I_C=500mA_{dc}, V_{CE}=2V_{dc}$)	20	---		
$V_{CE(sat)}$	Collector-Emitter Saturation Voltage ($I_C=150mA_{dc}, I_B=15mA_{dc}$)	---	0.4	Vdc	
	($I_C=500mA_{dc}, I_B=50mA_{dc}$)	---	0.75		
$V_{BE(sat)}$	Base-Emitter Saturation Voltage ($I_C=150mA_{dc}, I_B=15mA_{dc}$)	0.75	0.95	Vdc	
	($I_C=500mA_{dc}, I_B=50mA_{dc}$)	---	1.3		
f_T	Current Gain-Bandwidth Product ($V_{CE}=10.0V_{dc}, I_C=20mA_{dc}, f=100MHz$)	200	---	MHz	
C_{ob}	Output Capacitance ($V_{CB}=10V_{dc}, f=1.0MHz, I_E=0$)	---	8.5	pF	
t_d	Delay Time	$V_{CC}=30V, I_C=150mA, V_{BE}=2.00V, I_{B1}=15.00mA$		15	ns
t_r	Rise Time			20	ns
t_s	Storage Time	$V_{CC}=30V, I_C=150mA, I_{B1}=I_{B2}=15mA$		225	ns
t_f	Fall Time			30	ns

SOT-363



DIM	DIMENSIONS				NOTE
	INCHES		MM		
	MIN	MAX	MIN	MAX	
A	.006	.014	0.15	0.35	
B	.045	.053	1.15	1.35	
C	.085	.096	2.15	2.45	
D	.026		0.65Nominal		
G	.047	.055	1.20	1.40	
H	.071	.087	1.80	2.20	
J	---	.004	---	0.10	
K	.035	.043	0.90	1.10	
L	.010	.018	0.26	0.46	
M	.003	.006	0.08	0.15	






Fig. 1. Max Power Dissipation vs Ambient Temperature




Fig. 2. Collector Emitter Saturation Voltage vs. Collector Current




Fig. 3. Base-Emitter Voltage vs. Collector Current




Fig. 4. DC Current Gain vs. Collector Current




Fig. 5. Gain Bandwidth Product vs. Collector Current




Fig. 6. Typical Capacitance



Micro Commercial Components

Ordering Information :

Device	Packing
Part Number-TP	Tape & Reel; 3 Kpcs/Reel

Note : Adding "-HF" suffix for halogen free, eg. Part Number-TP-HF

IMPORTANT NOTICE

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes. **Micro Commercial Components Corp.** does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold **Micro Commercial Components Corp.** and all the companies whose products are represented on our website, harmless against all damages.

LIFE SUPPORT

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

CUSTOMER AWARENESS

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. **MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources.** MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.