

Micro Commercial Components



Micro Commercial Components 20736 Marilla Street Chatsworth CA 91311

Phone: (818) 701-4933 (818) 701-4939 Fax:

BDW93B

Features

- Halogen free available upon request by adding suffix "-HF" Intended for use in power linear and switching applications
- Lead Free Finish/RoHS Compliant (Note1) ("P" Suffix designates RoHS Compliant. See ordering information)
- Epoxy meets UL 94 V-0 flammability rating
- Moisure Sensitivity Level 1

Maximum Ratings

Mounting Torgue: 5 in-lbs Maximum

Symbol	Rating	Rating	Unit
V_{CEO}	Collector-Emitter Voltage	80	V
$V_{\sf CBO}$	Collector-Base Voltage	80	V
V_{EBO}	Emitter-Base Voltage	5.0	V
l _{CP}	Peak Collector Current	15	Α
lc	Collector Current	12	Α
Pc	Collector power dissipation	80	W
T_J	Junction Temperature	-55 to +150	°C
T_{STG}	Storage Temperature	-55 to +150	οС

Hectrical Characteristics @25°CUhless Cherwise Specified Symbol **Parameter** Min Max


~ j~ .				
OFFCHARA	CIENSTICS			
$V_{(BR)CEO}$	Collector-Emitter Breakdown Voltage (ξ =100mAdc, ξ =0)	80		Vdc
Сво	Collector-Base Cutoff Current $(V_{CB}=80Vdc,I_{E}=0)$		0.1	mAdc
I _{EBO}	Emitter-Base Cutoff Current		2.0	mAdc

CNCHARACTERISTICS

h _{FE-1}	Forward Current Transfer ratio $(b=3.0\text{Adc}, V_{\text{CE}}=3.0\text{Vdc})$	1000		
h _{FE-2}	Forward Current Transfer ratio $(\xi=5.0\text{Adc}, V_{\text{CE}}=3.0\text{Vdc})$	750	20000	
h _{FE-3}	Forward Current Transfer ratio $(\xi=10\text{Adc}, V_{\text{CE}}=3.0\text{Vdc})$	100		
V _{CE(sat)-1}	Collector-Emitter Saturation Voltage (b=5.0Adc, b=20mAdc)		2.0	Vdc
V _{CE(sat)-2}	Collector-Emitter Saturation Voltage (ξ =10Adc, ξ =100mAdc)		3.0	Vdc
V _{BE(sat)-1}	Base-Emitter Saturation Voltage (b=5.0Adc,le=20Adc)		2.5	Vdc
V _{BE(sat)-2}	Base-Emitter Saturation Voltage (b=10Adc,l₀=100Adc)		4.0	Vdc

Notes: 1. High Temperature Solder Exemption Applied, see EU Directive Annex 7.

NPN Silicon Power Transistors



	DIMENSIONS				
	INCHES		MM		
DIM	MIN	MAX	MIN	MAX	NOTE
Α	.560	.625	14.22	15.88	
В	.380	.420	9.65	10.67	
С	.140	.190	3.56	4.82	
D	.020	.045	0.51	1.14	
F	.139	.161	3.53	4.09	Ø
G	.190	.110	2.29	2.79	
Н		.250		6.35	
J	.012	.025	0.30	0.64	
K	.500	.580	12.70	14.73	
L	.045	.060	1.14	1.52	
N	.190	.210	4.83	5.33	
Q	.100	.135	2.54	3.43	
R	.080	.115	2.04	2.92	
S	.045	.055	1.14	1.39	
Т	.230	.270	5.84	6.86	
U		.050		1.27	
V	.045		1.15		,



Micro Commercial Components

Ordering Information:

Device	Packing
Part Number-BP	Bulk; 1 Kpcs/Box

Note: Adding "-HF" suffix for halogen free, eg. Part Number-BP-HF

IMPORTANT NOTICE

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes. **Micro Commercial Components Corp.** does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold **Micro Commercial Components Corp.** and all the companies whose products are represented on our website, harmless against all damages.

LIFE SUPPORT

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

CUSTOMER AWARENESS

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources. MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.