

PXTA44

NPN Silicon High Voltage Transistor

500mW

Features

- Halogen free available upon request by adding suffix "-HF"
- Low Collector-Emitter Saturation Voltage
- Epoxy meets UL 94V-0 flammability rating
- Moisture Sensitivity Level 1
- Lead Free Finish/RoHS Compliant("P" Suffix designates RoHS Compliant. See ordering information)

Mechanical Data


- Marking: A44

Maximum Ratings

Symbol	Rating	Rating	Unit
V_{CEO}	Collector-Emitter Voltage	400	V
V_{CBO}	Collector-Base Voltage	500	V
V_{EBO}	Emitter-Base Voltage	6	V
I_C	Collector Current	300	mA
P_C	Collector power dissipation	500	mW
T_J	Junction Temperature	-55 to +150	°C
T_{STG}	Storage Temperature	-55 to +150	°C

Electrical Characteristics @ 25°C Unless Otherwise Specified

Symbol	Parameter	Min	Typ	Max	Units
I_{CBO}	Collector Cutoff Current ($V_{CB} = 400V_{dc}, I_E = 0$)	---	---	100	nAdc
I_{EBO}	Emitter Cutoff Current ($V_{EB} = 4.0V_{dc}, I_C = 0$)	---	---	100	nAdc
BV_{CBO}	Collector-base breakdown voltage ($I_C = 100\mu A_{dc}, I_E = 0$)	500	---	---	Vdc
BV_{CEO}	Collector-emitter breakdown voltage ($I_C = 1mA_{dc}, I_B = 0$)	400	---	---	Vdc
BV_{EBO}	Emitter-base breakdown voltage ($I_E = 10\mu A_{dc}, I_C = 0$)	6	---	---	Vdc
h_{FE}	DC Current Gain ($I_C = 1mA_{dc}, V_{CE} = 10V_{dc}$) ($I_C = 10mA_{dc}, V_{CE} = 10V_{dc}$) ($I_C = 50mA_{dc}, V_{CE} = 10V_{dc}$) ($I_C = 100mA_{dc}, V_{CE} = 10V_{dc}$)	40 50 45 40	---	----- 200 ----- -----	--- --- --- ---
$V_{CE(sat)}$	Collector Saturation Voltage ($I_C = 1mA_{dc}, I_B = 0.1mA_{dc}$) ($I_C = 50mA_{dc}, I_B = 5mA$)	---	---	0.4 0.75	V V
$V_{BE(sat)}$	Collector Saturation Voltage ($I_C = 10mA_{dc}, I_B = 1mA_{dc}$)	---	---	0.75	V
C_{ob}	Collector output capacitance ($V_{CB} = 20V_{dc}, I_E = 0, f = 1MHz$)	---	---	7	pF





Micro Commercial Components

Ordering Information :

Device	Packing
Part Number-TP	Tape&Reel; 1 Kpcs/ Reel

Note : Adding "-HF" suffix for halogen free, eg. Part Number-TP-HF

IMPORTANT NOTICE

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes. **Micro Commercial Components Corp.** does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold **Micro Commercial Components Corp.** and all the companies whose products are represented on our website, harmless against all damages.

LIFE SUPPORT

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

CUSTOMER AWARENESS

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. **MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources.** MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.

www.mccsemi.com