



connection cables

7/8" male to female connector

RSM-RKM50-2M

- robust and pre-assembled round connector
- plastic moulding
- Degree of protection IP67
- also available with different cable lengths and of different materials

Wiring diagram



Type code	RSM-RKM50-2M
Ident no.	6914936
Connector A side	male connector, 7/8", straight
Number of pins	4 + PE
Contacts	metal, CuZn, gold-plated
Contact carriers	plastic, PUR, yellow
	sealing via contact carriers
Grip	plastic, TPU, yellow
	stainless steel coupling nut/screw available on request
Protection class	IP67, (screwed together)
Connector B side	female connector, 7/8", straight
Number of pins	4+PE
Contact carriers	plastic, PUR, yellow
	sealing via contact carriers
Contacts	metal, CuZn, gold-plated
Grip	plastic, TPU, yellow
Coupling nut/screw	metal, CuZn, nickel-plated
	stainless steel coupling nut/screw available on request
Protection class	IP67, only in screwed state
Cable diameter	7.3 mm
Cable length	2m
Cable sheath	PVC, yellow
Core insulation	PVC
Core colors	BK, BU, GNYE, BN, WH
Core cross-section	4x0.83mm ²
Core cross-section PE	1x0.83mm ²
Litz wire arrangement	19x0.25 mm
Litz wire design PE	19x0.25mm
Rated voltage [Umax]	300 V
Ampacity	9 A