


Accessories for fieldbus systems
Field-wireable connector
BSV8240-0/9


TURCK

Industrial
Automation





- M12 male
- Field-wireable
- 4-pole, angled, stainless steel coupling nut
- Cable outlet 4.0...8.0 mm
- For use in PROFIBUS-PA and FOUNDATION™ fieldbus applications

PROFIBUS-PA connection



FOUNDATION™ fieldbus connection



Type code	BSV8240-0/9
Ident no.	6914539
Connector A side	field-wireable male connector, M12 x 1, angled
Number of pins	4
Contacts	metal, CuZn, CuSnZn, Optalloy coated
Contact carriers	plastic, PA, black
Grip	plastic, PA, black
Coupling nut/screw	1.4404
Seal	plastic, FKM/FPM
Screw-in thread seal	plastic, NBR
Protection class	IP67, (screwed together)
External diameter of the cable	min. 4... 8mm
Core cross-section/Clamping ability	0.14...0.75mm ²
Screw-in thread	PG 9
Connection mode	screw/clamp connection
Pollution degree	3

Rated voltage [Umax]	250 V
Insulation resistance	≥ 10 ⁹ Ω
Ampacity	4 A
Forward resistance	≤ 5 mΩ
Ambient temperature Connector	-25... +90°C