

PROFIBUS-PA
Fieldbus display, 3 channel
FD-48-T317/EX

TURCK

Industrial
Automation



The 3-channel digital indicator FD-48-T317/EX displays the process information of the fieldbus nodes of a PROFIBUS-PA network.

The device (listener) receives and displays the values of the adjusted fieldbus addresses. Parameterization is code word protected and implemented via a keypad on the front side. Adjustments can be done for each port separately. The process value of the actuator/sensor is displayed as a 5-digit number and the process value status is displayed via limit value markers.

Apart from a measuring value indicator, the display contains a 41-segment bargraph for trend monitoring, which can be scaled separately from the display value.

The FD-48-T317/EX performs as a "listener", i.e. initialization by the host is not required (integration via software redundant) and does not appear in the network as a node with an own address.

The device is supplied with power by the fieldbus (< 10 mA) and can be applied in Ex areas up to temperatures of the class T6.


- **Entity and FISCO compliant according to IEC TS 60079-27**
- **Digital fieldbus display for the indication of process values**
- **powder-coated die-cast aluminium housing**
- **Connection of the housing potential via external earthing**

PROFIBUS-PA

Fieldbus display, 3 channel

FD-48-T317/EX

Dimensions



Type code	FD-48-T317/EX
Ident no.	6901315
Fieldbus standard	IEC 61158-2
Operating voltage range	9...30 VDC
Current self-consumption	≤ 10 mA
Indication	
Display	LCD, 5-digit, 7-segment
Ex approval acc. to conformity certificate	TÜV 07 ATEX 553588
Max. input voltage U_i	≤ 30 V
Max. input current I_i	≤ 660 mA
Max. input power P_i	≤ 1600 mW
Internal inductance/capacitance L/C,	negligible
Device designation	Ⓢ II 2 (1) G EEx ia IIC T6 resp. T5 Ⓢ II 2 D IP65 T70°C FISCO / Entity field device
Electrical connection	Cable glands
Terminal cross-section	2.5 mm ²
Protection class	IP66
Ambient temperature	-10...+60 °C
Housing material	powder-coated die-cast aluminium
Housing color	Black
Dimensions	140x 140x 71 mm
Connection mode	Wall mounting