

9X14 PECL J-LEAD CLOCK- PB FREE COMPLIANT (SEE PAGE TWO FOR PART NUMBERING SCHEME)

■ APPROVALS

RALTRON	CUSTOMER
Eng. approval, date: RONEN 3/20/03	Name (please print):
Sales approval, date:	Title (please print):
Created by, date: RONEN 3/20/03	Signature, date:
Revision:	

■ MECHANICAL SPECIFICATION

6 pin Version	4 pin Version	OUTLINE TOLERANCE: ±0.015" / 0.4mm (Unless otherwise specified)
		<p>PIN FUNCTIONS (6 pins): [1] NC OR COMP. OUTPUT [2] EN / DIS OR NC [3] CASE / GROUND [4] OUTPUT [5] COMP. OUTPUT OR NC [6] SUPPLY VOLTAGE</p> <p>PIN FUNCTIONS (4 pins): [1] E / D OR N/C OR COMP. OUT [2] CASE / GROUND [3] OUTPUT [4] SUPPLY VOLTAGE</p> <p>MARKING (EXAMPLE): CE8950A-LZ 155.520-T-C-EL RAL D/C</p>

■ ELECTRICAL SPECIFICATION

PARAMETER	SYMBOL	CONDITIONS	VALUE	UNIT
Frequency, nom	fo	-	70.000~250.0	MHz
Supply voltage, nom.	Vcc	Vcc±5%	3.3VDC 5.0VDC	V
Supply current, max. (excluding load)	Is	Vcc=+3.3VDC/+5.0VDC Ta=+25°C, 50Ω to Vcc-2.0VDC load	100	mA
PECL output level	VOH / VOL	Vcc=+3.3VDC/+5.0VDC load=50Ω to Vcc-2.0VDC	2.275 / 1.68 3.975/3.38	V
Duty cycle	DC	load=50Ω to Vcc-2.0VDC / @50%Vcc, Ta=+25°C	40...60 OR 45...55	%
Rise- / fall time, max.	tr / tf	20%~80% Vout, 80%~20% Vout, max	0.100...1.0 (see note A)	ns
Jitter, rms, max.	J	1σ, Fj=12KHz...20MHz	1.0	ps
Overall freq. stability, max.	Δf/fc	Including operating temperature, ±5% load & supply variations, calibration @+25°C, and 10 year aging	SEE PART NUMBER GENERATION TABLE	ppm
Enable option	En	Pin 2=Low, Vcc-1.620 (max.)	Enabled	-
Disable option	Dis	Pin 2=High, Vcc-1.025 (min.)	Pin 4 will assume a fixed level of logic "0", and pin 5 will assume a fixed level of logic "1"	-
Operating temperature range	Ta	-	SEE PART NUMBER GENERATION TABLE	°C
Storage temperature range	T(stg)	-	-55...+90	°C
Absolute voltage range	Vcc(abs)	Non-destructive, DC	-0.5...+7.0	V

3/20/03 marketing-rfq, clock

NOTE A: RISE AND FALL TIME VALUES (tr/TF) ARE FREQUENCY DEPENDENT.

