

## VC7000 Series- General Specification

### n APPROVALS

RALTRON	CUSTOMER
Eng. approval, date: Luis Vargas 12/09/02	Name (please print):
Sales approval, date: Tod Raphaely Dec 9,02	Title (please print):
Created by, date:	Signature, date:
Revision:	

### n ELECTRICAL SPECIFICATION:

Note 1: measurements are done @ Tamb = +25°C = 15 pF to ground; unless otherwise noted

Note 2: Fo is the actual output frequency measured during Accuracy test

Note 2: frequencies above 52 MHz use straight multiplication design

PARAMETER	SYMBOL	CONDITIONS	VALUE	UNIT
Frequency, nom	fn	-	1.000.....160.000	MHz
Supply voltage, nom.	Vcc	Vcc±5%	<b>3.3VDC 5.0VDC</b>	VDC
Supply current	Is	-	25.0.....60.0	mA
Freq. stability vs. temperature, max.	Δf/fc (Ta)	(ref. to +25°C)	SEE PART NUMBER GENERATION TABLE	ppm
Freq. stability vs. supply changes, max.	Δf/fc (ΔVs)	Supply change, ±5%	±5.0	ppm
Freq. stability vs. load changes, max.	Δf/fc (Δload)	Load change, ±10%	±3.0	ppm
Aging characteristics, max.	Δf/fc (Δt)	Δt=1 <sup>st</sup> year	±4.0	ppm
	Δf/fc (Δt)	Δt=per year thereafter	±2.0	ppm
HCMOS output levels	VOH / VOL	-	2.97 / 0.3 4.5 / 0.5	V
Duty cycle	DC	@ 50%Vcc	SEE PART NUMBER GENERATION TABLE	%
Rise- / fall time, max.	tr / tf	20%~80% Vout, 80%~20% Vout	2.0...10.0 (see note A)	ns
Control voltage range	Vc	DC	0...+3.3 +0.5...+4.5	V
Pullability	ΔF/Fo	-	SEE PART NUMBER GENERATION TABLE	ppm
Linearity, max.	Δf/V	Positive slope	≤ 10	%
Input impedance, min.	Zin	-	≥ 10	KΩ
Modulation freq. bandwidth, min.	MBW (-3dB)	-	≥ 10	KHz
Operating temperature range	Ta	-	SEE PART NUMBER GENERATION TABLE	°C
Storage temperature range	T(stg)	-	-45...+120	°C
Absolute voltage ranges	Vcc,Vc(abs)	Non-destructive, DC	-0.5...+7.0	V

### n MECHANICAL SPECIFICATION

