

# High Power Water Cooled Laser Stack

Wavelength  $1532.5 \pm 10$  nm

Princeton Lightwave offers a series of high power 1532 nm stacks. An MQW laser structure assures high power.



## Features

- Power to 300 W cw

## Applications

- High power pump for defense and medical applications

### Key Product Specifications Long Wavelength Stacked Array

Model**	HP1-2D-2F	HP3-2D-2F	units
Power (cw)	100	300	W
Peak Wavelength	$1532.5 \pm 10$	$1532.5 \pm 10$	nm
Spectral Width	8	8	nm
Wavelength Locked	No	No	No
Operating Voltage	5.2	13	V
Operating Current	110	110	A
Threshold Current	<20	<20	A
Slow Axis Div. (FWHM)	<10°	<10°	degrees
Fast Axis Div. (FWHM)	42°	42°	deg./mrad
Element Width	100	100	μm
Elements/Arrays	15-20	15-20	
Number of Arrays	4	10	
Bar Pitch	1.8	1.8	mm
Polarization	TE	TE	
Flow Rate	1.6	4	liter/min
Operating Temperature	15	15	deg. C

Notes:

§ 70% of the power in this interval

\* Estimated value based on 10 stack array

\*\* Reliability currently under investigation

Power 100, 300

**Princeton Lightwave, Inc.**  
 2555 Route 130 South Suite 1, Cranbury, NJ 08512  
 Tel: 609.495.2600  
 Fax: 609.395.9114  
 email: sales@princetonlightwave.com  
 website: www.princetonlightwave.com

Princeton Lightwave, Inc. reserves the right to make changes to the product(s) and information contained herein without notice. No liability is assumed by Princeton Lightwave as a result of the use or application of this product.



Copyright 2005 Princeton Lightwave, Inc.  
 All rights reserved.