

66228 3C91C TYPE PROTON RADIATION TOLERANT OPTOCOUPLER



09/22/2010

Features:

- High Reliability
- Base lead eliminated for improved noise immunity
- Rugged package
- Stability over wide temperature
- +500 V electrical isolation

Applications:

- Eliminate ground loops
- Level shifting
- Line receiver
- Switching power supplies
- Motor control

DESCRIPTION

The **66228** optocoupler consists of an 850 nm GaAlAs LED optically coupled to a silicon planar phototransistor. This LED has proven to be highly tolerant to proton radiation and to be more tolerant of operating temperatures over 100°C than the more commonly used 660 nm LED. The optocoupler is built on a TO-72 header. The anode of the LED is electrically connected to the case. The internal base connection has been eliminated for improved noise immunity.


ABSOLUTE MAXIMUM RATINGS

Emitter-Collector Voltage	7 V
Collector-Emitter Voltage	60 V
Reverse Input Voltage	7 V
Input Diode Continuous Forward Current (Note 1)	50 mA
Peak Forward Input Current (value applies for $t_w \leq 1\mu s$, PRR < 300 pps)	500 mA
Continuous Collector Current	50 mA
Continuous Transistor Power Dissipation (Note 2)	230 mW
Input to Output Isolation Voltage	1000 V
Storage Temperature	-65°C to +150°C
Operating Free-Air Temperature Range	-55°C to +125°C
Lead Solder Temperature (10 seconds, 1/16" from case)	260°C


Notes:

1. Derate linearly to 125°C free-air temperature at the rate of 0.5 mA/°C.
2. Derate linearly to 125°C free-air temperature at the rate of 2.3 mW/°C.

Package Dimensions



Schematic Diagram



66228

09/22/2010

3C91C TYPE PROTON RADIATION TOLERANT OPTOCOUPLER**ELECTRICAL CHARACTERISTICS**T_A = 25°C unless otherwise specified.

PARAMETER	SYMBOL	MIN	TYP	MAX	UNITS	TEST CONDITIONS
Input Diode Static Reverse Current	I _R			1	μA	V _R = 3 V
Input Diode Static Forward Voltage	V _F		1.15	1.2	V	I _F = 2 mA
Input Diode Static Forward Voltage	V _F		1.5	1.8	V	I _F = 50 mA
Reverse Breakdown Voltage	B _{VR}	6	12		V	I _R = 8 μA
Input Diode Capacitance	C _{IN}		25		pF	V = 0 V, f = 1 MHz

OUTPUT TRANSISTORT_A = 25°C unless otherwise specified.

PARAMETER	SYMBOL	MIN	TYP	MAX	UNITS	TEST CONDITIONS
Collector-Emitter Breakdown Voltage	V _{(BR)CEO}	50			V	I _C = 1 mA, I _B = 0, I _F = 0
Emitter-Collector Breakdown Voltage	V _{(BR)ECO}	7			V	I _C = 10 μA, I _E = 10 μA, I _F = 0
Collector-Emitter Dark Current	I _{CEO1} I _{CEO2}			50 10	nA nA	V _{CE} = 50 V, I _F = 0 mA V _{CE} = 5 V, I _F = 0 mA

COUPLED CHARACTERISTICST_A = 25°C unless otherwise specified.

PARAMETER	SYMBOL	MIN	TYP	MAX	UNITS	TEST CONDITIONS
On State Collector Current	I _{C(ON)}	4			mA	V _{CE} = 5 V, I _F = 10 mA
On State Collector Current	I _{C(ON)}	3		20	mA	V _{CE} = 0.4 V, I _F = 10 mA
On State Collector Current -55°C	I _{C(ON)}	2			mA	V _{CE} = 5 V, I _F = 10 mA
Collector-Emitter Saturation Voltage	V _{CE(SAT)}			0.4	V	I _F = 50 mA, I _C = 10 mA
Isolation Resistance	R _{ISO}	10 ⁹			Ω	V _{IN-OUT} = 1000 V
Input to Output Capacitance	C _{IO}		2	2.5	pF	f = 1 MHz
Delay Time	t _d		2	4	μs	V _{CE} = 5 V, I _F = 2 mA, R _L = 100 Ω
Storage Time	t _s		0.2	0.5	μs	V _{CE} = 5 V, I _F = 2 mA, R _L = 100 Ω
Rise Time	t _r		3	5	μs	V _{CE} = 5 V, I _F = 2 mA, R _L = 100 Ω
Fall Time	t _f		4	5	μs	V _{CE} = 5 V, I _F = 2 mA, R _L = 100 Ω

RECOMMENDED OPERATING CONDITIONS:

PARAMETER	SYMBOL	MIN	MAX	UNITS
Input Current, Low Level	I _{FL}	0	1	μA
Input Current, High Level	I _{FH}	2	10	mA
Supply Voltage	V _{CE}	5	50	V
Operating Temperature	T _A	-55	125	°C

SELECTION GUIDE

PART NUMBER	PART DESCRIPTION
66228-001	Commercial
66228-101	Screened