


MTS/MDA

SENSOR, DATA ACQUISITION BOARDS

- Selection of 3 Standard Sensor/DAQ Boards
- MoteWorks™ Drivers Support Sensor Readings
- Supports IRIS, MICAz and MICA2 Motes
- Individual Power Control for Each Sensor

Applications


- Vibration and Magnetic Anomaly Detection
- External Sensor Connection
- Localization and Acoustic Tracking
- Robotics
- Wireless Sensor Networking



MTS310CB

MTS310


The MTS310 is a flexible sensor board with a variety of sensing modalities. These modalities include a Dual-Axis Accelerometer, Dual-Axis Magnetometer, Light, Temperature, Acoustic and Sounder. The MTS310 is for use with the IRIS, MICAz and MICA2 Motes.



MTS300CB

MTS300

The MTS300CB is a flexible sensor board with a variety of sensing modalities. These modalities include Light, Temperature, Acoustic and Sounder. The MTS300CB is for use with the IRIS, MICAz and MICA2 Motes.



MDA100CB

MDA100

The MDA100CB sensor and data acquisition board has a precision thermistor, a light sensor/photocell and general prototyping area. Designed for use with the IRIS, MICAz and MICA2 Motes, the prototyping area supports connection to all 51 pins on the expansion connector, and provides an additional 42 unconnected solder points for breadboarding.

Ordering Information

Model	Description
MTS310CB	Light, Temperature, Acoustic, Sounder, Dual-Axis Accel and Dual-Axis Mag Sensor Board
MTS300CB	Light, Temperature, Acoustic and Sounder Sensor Board
MDA100CB	Light, Temperature, Prototype Area Sensor/DAQ Board