

## 6-18GHz Low Noise Digital Variable Amplifier

### GaAs Monolithic Microwave IC

#### Description



The CHA3512 is composed by a Single Pole Double Through (SPDT) switch followed by a one step digital attenuator and a double stage travelling wave amplifier. It is designed for defense applications. The backside of the chip is both RF and DC grounded. This helps to simplify the assembly process.

The circuit is manufactured with a pHEMT process, 0.25 $\mu$ m gate length, via holes through the substrate, air bridges and electron beam gate lithography.

It is available in chip form.

#### Main Features

- Performances: 6-18GHz
- 23dBm saturated output power
- 16dB gain
- 1 bit attenuator for 20dB dynamic range
- DC power consumption: 210mA @ 4.5V
- Chip size: 4.27 x 2.46 x 0.1mm



**Typical on wafer Measurements**  
Gain versus attenuation states

#### Main Characteristics

Tamb. = 25°C

Symbol	Parameter	Min	Typ	Max	Unit
Fop	Operating frequency range	6		18	GHz
G	Small signal gain @ Attenuator state 0dB		16		dB
Psat	Saturated Output power @ Attenuator state 0dB		23		dBm
ATT dyn	Attenuator range		20		dB

ESD Protection: Electrostatic discharge sensitive device. Observe handling precautions !

**Electrical Characteristics on wafer**

Tamb = +25°C

Vd = Pads B, D = 4.5V, Vg = Pads A, C tuned for Id = 210mA

Symbol	Parameter	Min	Typ	Max	Unit
Fop	Operating frequency range (1)	6		18	GHz
G	Small signal gain @ Attenuator state 0dB (1)		16		dB
	6-16GHz	14	16		
	16-18GHz	10	13		
ATT dyn	Attenuator range	19	20	22	dB
Is	Isolation @ Attenuator state 0dB & switch OFF (1)	-25	-35		dB
P1dB	Output power at 1dB compression @ Attenuator state 0dB (1)		20		dBm
Psat	Saturated Output power @ Attenuator state 0dB (1)		23		dBm
NF	Noise figure @ Attenuator state 0dB		7		dB
RL_IN	Input Return Loss all attenuator states (switch ON)		-15	-8	dB
RL_OUT	Output Return Loss all attenuator states (switch ON and switch OFF)		-20	-6	dB
Vd	Drain bias DC voltage (Pads B, D)		4.5		V
Id	Bias current @ small signal		210	250	mA
Vc	Control voltage for Attenuator bit & SPDT switch	-5		0	V

(1) These values are representative for on-wafer measurements that are made without bonding wires at the RF ports.

## Absolute Maximum Ratings

Tamb. = 25°C (1)

Symbol	Parameter	Values	Unit
Vd	Maximum Drain bias voltage ( Pads B, D)	+5	V
Id	Drain bias current with Vd=4.5V	300	mA
Vg	Gate bias voltage (Pads A,C)	-2 to +0.4	V
Vc	Attenuator bit & SPDT control voltage	-7 to +0.6	V
Pin	Maximum input power overdrive (2)	+20.0	dBm
Tch	Maximum channel temperature	+175	°C
Ta	Operating temperature range	-40 to +70	°C
Tstg	Storage temperature range	-55 to +125	°C

(1) Operation of this device above anyone of these parameters may cause permanent damage.

(2) Duration < 1s.

Thermal Resistance channel to ground paddle =123°C/W for Tamb. = +70°C.


## LNA Control interface

The attenuator state is controlled by 2 voltages. The SPDT switch is controlled by 2 voltages.


state	Theoretical attenuation (dB)	Voltage CONTROL PAD		Switch control	
		20A (V)	20B (V)	E (V)	F (V)
0	0 référence	-5	0	-5	0
1	20	0	-5	-5	0
2	Isolation	-5	0	0	-5

## Typical on wafer Measurements @ 25°C


Bias conditions:  $V_d = 4.5V$ ,  $V_g$  tuned for  $I_d = 210mA$




Linear Gain versus attenuator states




Linear Gain with SPDT switch OFF




Saturated output power@nominal state



Attenuator accuracy versus frequency




dB(S11) versus frequency for all states




dB(S22) versus frequency for all states

**Typical test fixture Measurements @ 25°C**


Bias conditions:  $V_d = 4.5V$ ,  $V_g$  tuned for  $I_d = 210mA$




Linear Gain versus attenuation states



Input Return Loss versus attenuation states






Output Return Loss versus attenuation states

## Typical Chip on wafer Sij parameters for reference state

Tamb = +25°C, Vd = +4.5 V, Id = 210 mA, 0dB state (20A = -5V, 20B = 0V).

Freq (GHz)	dB(S11)	P(S11) (°)	dB(S21)	P(S21) (°)	dB(S12)	P(S12) (°)	dB(S22)	P(S22) (°)
1.0	-5.5	-92.5	-20.7	161.9	-62.1	112.2	-0.5	-57.6
1.5	-8.0	-124.4	-2.7	69.1	-66.5	-40.1	-1.2	-85.9
2.0	-11.1	-149.5	0.3	94.1	-68.7	91.4	-1.5	-107.3
2.5	-13.9	-167.5	10.0	50.3	-64.9	14.8	-1.9	-132.8
3.0	-17.9	170.0	13.8	-2.9	-83.1	140.3	-2.8	-157.7
3.5	-25.6	167.5	15.6	-54.8	-87.8	39.6	-4.7	-175.7
4.0	-28.0	-112.8	16.3	-91.9	-73.1	116.8	-6.1	167.0
4.5	-20.8	-106.6	17.1	-127.4	-67.2	82.5	-8.0	152.1
5.0	-17.8	-121.1	17.6	-161.5	-63.8	57.4	-10.0	140.7
5.5	-16.9	-137.3	18.0	165.7	-61.5	22.6	-12.2	132.5
6.0	-17.4	-152.0	18.2	133.9	-60.0	-7.1	-14.5	127.7
6.5	-19.4	-161.4	18.3	103.0	-57.6	-33.7	-16.7	127.0
7.0	-22.7	-156.8	18.3	72.7	-56.5	-63.6	-18.7	129.8
7.5	-23.3	-123.6	18.2	43.1	-55.2	-89.9	-19.7	136.0
8.0	-19.3	-107.8	18.0	14.2	-54.0	-115.4	-20.2	140.3
8.5	-15.6	-107.5	17.8	-13.9	-53.6	-142.5	-21.1	137.2
9.0	-13.3	-118.9	17.5	-41.2	-53.7	-160.6	-21.5	132.1
9.5	-11.7	-131.3	17.3	-68.0	-52.6	-177.3	-22.9	127.6
10.0	-10.5	-147.0	17.1	-94.5	-51.6	153.2	-24.4	126.2
10.5	-10.2	-161.0	16.9	-120.6	-53.2	131.7	-26.5	125.0
11.0	-10.0	-174.3	16.9	-146.6	-53.3	114.2	-28.6	130.5
11.5	-10.1	172.0	16.9	-173.0	-53.7	99.0	-29.8	142.9
12.0	-10.4	157.6	17.0	159.8	-55.4	76.4	-29.7	148.2
12.5	-11.1	142.7	17.0	131.8	-59.3	61.7	-30.1	140.1
13.0	-12.4	125.9	17.0	102.9	-59.3	48.4	-32.0	109.0
13.5	-14.7	112.4	16.8	74.2	-62.4	-22.1	-34.9	37.3
14.0	-17.6	104.1	16.7	45.8	-59.0	-113.2	-29.6	-36.7
14.5	-20.9	107.6	16.6	16.4	-54.6	-169.8	-25.4	-71.4
15.0	-20.5	120.0	16.6	-14.5	-51.5	171.1	-24.5	-93.5
15.5	-18.4	113.6	16.4	-46.8	-48.0	149.4	-25.2	-99.5
16.0	-16.8	92.0	16.1	-80.4	-45.8	126.8	-25.9	-79.2
16.5	-15.7	63.4	15.5	-114.6	-43.8	100.8	-21.5	-60.8
17.0	-14.9	31.3	14.7	-148.5	-43.3	75.6	-15.9	-66.5
17.5	-14.5	2.8	14.0	175.9	-42.6	52.2	-12.2	-84.5
18.0	-13.8	-20.5	12.9	138.1	-42.4	25.5	-9.6	-106.7
18.5	-12.8	-39.8	11.3	98.1	-43.0	-5.1	-8.4	-131.5
19.0	-11.5	-57.4	8.9	59.2	-45.7	-39.8	-8.3	-154.4
19.5	-10.3	-75.6	6.0	23.7	-50.7	-77.9	-8.9	-174.8
20.0	-9.3	-93.4	3.2	-8.9	-60.5	-154.2	-10.2	167.0
20.5	-8.7	-110.5	0.8	-40.4	-57.9	108.5	-12.1	151.2
21.0	-8.4	-127.9	-0.9	-74.3	-50.5	78.2	-15.0	138.3
21.5	-8.4	-144.2	-1.8	-118.3	-47.7	52.1	-21.2	150.9
22.0	-8.6	-159.1	-3.7	176.5	-44.3	19.4	-15.1	-171.3
22.5	-8.9	-175.4	-8.9	108.2	-45.6	-14.4	-12.2	157.4
23.0	-9.5	167.6	-13.6	57.0	-47.3	-35.8	-12.7	134.3
23.5	-10.4	150.2	-16.4	15.7	-49.2	-46.6	-13.9	117.4
24.0	-11.6	130.5	-18.1	-17.7	-52.6	-62.7	-15.2	103.7

**Chip Assembly and Mechanical Data**




Note: RF wire bondings should be as short as possible, lower than 0.35mm.  
25µm diameter gold wire is to be preferred.

**Recommended circuit bonding table**

Label	Type	Decoupling	Comment
20A, 20B	Vc	Not required	20dB attenuator control
<b>B</b>	<b>Vd</b>	<b>120pF / 10nF</b>	<b>Drain Supply</b>
<b>D</b>	<b>Vd</b>	<b>120pF / 10nF</b>	<b>Drain Supply</b>
A	Vg	Not required	Gate Supply
C	Vg	Not required	Gate Supply
E, F	Vc	Not required	Switch control

## Bonding pad positions



Chip thickness: 100μm

UNITS : μm  
Tol : ±35μm

## Ordering Information

Chip form : CHA3512-99F/00

**Elettronica S.p.A** has the intellectual property of this MMIC and gives to **United Monolithic Semiconductors S.A.S.** non-exclusive license to sell it.

Information furnished is believed to be accurate and reliable. However **United Monolithic Semiconductors S.A.S.** assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of **United Monolithic Semiconductors S.A.S.** Specifications mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information previously supplied. **United Monolithic Semiconductors S.A.S.** products are not authorised for use as critical components in life support devices or systems without express written approval from **United Monolithic Semiconductors S.A.S.**