

Schottky Barrier Rectifiers

Using the Schottky Barrier principle with a Molybdenum barrier metal. These state-of-the-art geometry features epitaxial construction with oxide passivation and metal overlay contact. Ideally suited for low voltage, high frequency rectification, or as free wheeling and polarity protection diodes.

Features

- * Low Forward Voltage.
- * Low Switching noise.
- * High Current Capacity
- * Guarantee Reverse Avalanche.
- * Guard-Ring for Stress Protection.
- * Low Power Loss & High efficiency.
- * 150°C Operating Junction Temperature
- * Low Stored Charge Majority Carrier Conduction.
- * Plastic Material used Carries Underwriters Laboratory Flammability Classification 94V-O



* In compliance with EU RoHs 2002/95/EC directives
The marking is indicated by part no. with. "M". ex:SR302M~SR306M

MAXIMUM RATINGS

Characteristic	Symbol	SR					Unit
		302	303	304	305	306	
Peak Repetitive Reverse Voltage Working Peak Reverse Voltage DC Blocking Voltage	V_{RRM} V_{RWM} V_R	20	30	40	50	60	V
RMS Reverse Voltage	$V_{R(RMS)}$	14	21	28	35	42	V
Average Rectifier Forward Current	I_O	3.0					A
Non-Repetitive Peak Surge Current (Surge applied at rate load conditions half-wave, single phase,60Hz)	I_{FSM}	75					A
Junction Operating Temperature Range Storage Temperature (1)	T_J T_{STG}	-65 to +150 20~35 °C 、 30%~60% RH					°C


(1)expired date : 1 year

ELECTRIAL CHARACTERISTICS

Characteristic	Symbol	SR					Unit
		302	303	304	305	306	
Maximum Instantaneous Forward Voltage ($I_F = 3.0$ Amp)	V_F	0.550			0.700		V
Maximum Instantaneous Reverse Current (Rated DC Voltage, $T_C = 25^\circ\text{C}$) (Rated DC Voltage, $T_C = 125^\circ\text{C}$)	I_R	0.5 20					mA
Typical Junction Capacitance (Reverse Voltage of 4 volts & $f=1$ MHz)	C_P	210			190		pF

SCHOTTKY BARRIER RECTIFIERS

**3.0 AMPERES
20-60 VOLTS**



DIM	MILLIMETERS	
	MIN	MAX
A	5.00	5.60
B	25.40	---
C	7.20	9.50
D	1.20	1.30

CASE---
Transfer molded plastic

POLARITY---
Cathode indicated polarity band

SR302 Thru SR306

FIG-1 FORWARD CURRENT DERATING CURVE




FIG-2 TYPICAL FORWARD CHARACTERISTICS




FIG-3 TYPICAL REVERSE CHARACTERISTICS




FIG-4 TYPICAL JUNCTION CAPACITANCE




FIG-5 PEAK FORWARD SURGE CURRENT

