



PRELIMINARY

SOLID STATE DEVICES, INC

14849 Firestone Boulevard · La Mirada, CA 90638
Phone: (714) 670-SSDI (7734) · Fax: (714) 522-7424SDR950CT/3
thru
SDR952CT/3


Designer's Data Sheet

FEATURES:

- Hyper Fast Recovery: 35 nsec Maximum
- High Surge Rating
- Low Reverse Leakage Current
- Low Junction Capacitance
- Hermetically Sealed Package
- Gold Eutectic Die Attach available
- Ultrasonic Aluminum Wire Bonds
- Available in Common Anode and Doubler versions:
Common Anode: SDR950CT/3-SDR952CT/3
Doubler: SDR950DCT/3-SDR952DCT/3
- TX, TXV and Space Level Screening Available

120 AMP
100-200 VOLTS
35 nsec
HYPER FAST
COMMON CATHODE
CENTERTAP RECTIFIER

TO-3



MAXIMUM RATINGS

RATING	SYMBOL	VALUE	UNIT
Peak Repetitive Reverse and DC Blocking Voltage SDR950CT/3 SDR951CT/3 SDR952CT/3	VRRM VRWM VR	100 150 200	Volts
Average Rectified Forward Current (Resistive Load, 60Hz, Sine Wave, TA=25°C)	IO	120	Amps
Peak Surge Current (8.3 ms Pulse, Half Sine Wave, TA=25°C) note 1	IFSM	600	Amps
Operating and storage temperature	Top & Tstg	-65 to +200	°C
Maximum Thermal Resistance Junction to Case, each individual diode Junction to Case, both legs tied together	RθJC	1.0 0.65	°C/W

note 1 Per leg.

NOTE: All specifications are subject to change without notification.
SCD's for these devices should be reviewed by SSDI prior to release.

DATA SHEET#: RH0129 B

SDR950CT/3 thru SDR952CT/3

PRELIMINARY



SOLID STATE DEVICES, INC



14849 Firestone Boulevard · La Mirada, CA 90638
Phone: (714) 670-SSDI (7734) · Fax: (714) 522-7424

ELECTRICAL CHARACTERISTICS (Per leg)

CHARACTERISTICS	SYMBOL	MAXIMUM	UNIT
Instantaneous Forward Voltage Drop (IF = 25 Adc, TA=25°C, 300μs Pulse) (IF = 50 Adc, TA=25°C, 300μs Pulse)	VF	0.95 1.05	Vdc
Instantaneous Forward Voltage Drop (IF = 25 Adc, TA= 100°C, 300μs Pulse) (IF = 25 Adc, TA= - 55°C, 300μs Pulse)	VF	0.85 1.20	Vdc
Reverse Leakage Current (Rated VR, TA=25°C, 300μs pulse minimum)	IR	100	μA
Reverse Leakage Current (Rated VR, TA=100°C, 300μs pulse minimum)	IR	10	mA
Junction Capacitance (VR = 10 Vdc, TA=25°C, f= 1 MHz)	CJ	450	pf
Reverse Recovery Time (IF=500mA, IR=1 A, IRR=250mA, TA=25°C)	trr	35	nsec

CASE OUTLINE: TO-3

ASE: CATHODE
PIN 1: ANODE 1
PIN 2: ANODE 2



TYPICAL OPERATING CURVES

TA=25°C Unless otherwise specified

