


FEATURES

- CRACK RESISTANT TERMINATION
- SOFT TERMINATION, OPEN MODE FAILURE
- WIDE VOLTAGE RANGE (16V TO 5KV)
- HIGH CAPACITANCE (UP TO 10 μ F)
- RoHS COMPLIANT
- SAC SOLDER COMPATIBLE**

RoHS Compliant

Includes all homogeneous materials

*See Part Number System for Details




Temperature Coefficient	NPO	X7R
Capacitance Range	5pF ~ 0.22 μ F	180pF ~ 10 μ F
Capacitance Tolerance	For 2.2pF ~ 10pF: ± 0.1 pF (B), ± 0.25 pF (C), ± 0.5 pF (D), ± 1 pF (F) Above 10pF: $\pm 1\%$ (F), $\pm 2\%$ (G), $\pm 5\%$ (J), $\pm 10\%$ (K)	$\pm 10\%$ (K) & $\pm 20\%$ (M)
Operating Temperature Range	-55°C ~ +125°C	
Temperature Characteristics	± 30 ppm/°C	$\pm 15\%$ Δ Cap.
Rated Voltages	16Vdc, 25Vdc, 50Vdc, 100Vdc, 200Vdc, 250Vdc, 500Vdc, 630Vdc, 1KVdc, 2Kvdc, 3Kvdc & 5Kvdc	
Q or Dissipation Factor	Q = ≥ 1000 (more than 30pF)* Q = $\geq 400 + 20 \times C$ in pF (30pF and below)*	2.5% max. @ 1KHz, 1.0V $\pm$ 0.2Vrms
Insulation Resistance	10,000Megohm or 500Megohm/ μ F whichever is less @ +25°C	
Dielectric Withstanding Voltage	200% of rated voltage for 5 seconds, 50mA max. (16V ~ 250V) 150% of rated voltage for 5 seconds, 50mA max. (500V ~ 630V) 120% of rated voltage for 5 seconds, 50mA max. (1KV ~ 5KV)	


*Test Frequency & Voltage: Up to 100pF 1MHz/1.0Vrms, Above 100pF 1KHz/1.0Vrms

**Reflow soldering is recommended. Contact NIC regarding the use of other soldering methods.


PART NUMBER SYSTEM



CONSTRUCTION



OPEN MODE FAILURE AS A RESULT OF BENDING STRESS



NPO VALUES AND SIZES (mm)

EIA Case Size	0603				0805				1206								1210							
Length (L)	1.60 ± 0.1				2.00 ± 0.2				3.20 ± 0.3								3.20 ± 0.30							
Width (W)	0.80 ± 0.1				1.25 ± 0.25				1.60 ± 0.2								2.50 ± 0.20							
Thickness max. (T)	0.90 max.				1.45 max.				1.80 max.								2.60 max.							
Termination Width (P)	0.15 min.				0.20 min.				0.30 min.								0.30 min.							
Capacitance	Working Voltage (Vdc)																							
	200	16	25	50	200	250	500	16	25	50	200	250	500	1K	2K	3K	16	25	50	200	250	500		
5.0																								
8.2																								
10																								
12																								
15																								
18																								
22																								
27																								
33																								
39																								
47																								
56																								
68																								
82																								
100																								
120																								
150																								
180																								
220																								
270																								
330																								
390																								
470																								
560																								
680																								
820																								
0.001µF																								
0.0012																								
0.0015																								
0.0018																								
0.0022																								
0.0027																								
0.0033																								
0.0039																								
0.0047																								
0.0056																								
0.0068																								
0.0082																								
0.01µF																								
0.012																								
0.015																								
0.018																								
0.022																								
0.027																								
0.033																								
0.039																								
0.047																								
0.056																								
0.068																								
0.1µF																								



NPO VALUES AND SIZES (mm)

EIA Case Size	1808				1812						1825			2220	
Length (L)	4.60 ± 0.3				4.60 ± 0.3						4.60 ± 0.3			5.70 ± 0.4	
Width (W)	2.00 ±0.2				3.20 ±0.3						6.35 ±0.4			5.00 ±0.4	
Thickness max. (T)	2.20 max.				3.00 max.						2.60 max.			3.00 max.	
Termination Width (P)	0.30 min.				0.30 min.						0.30 min.			0.30 min.	
Capacitance	Working Voltage (Vdc)														
	1K	2K	3K	5K	16	25	50	1K	2K	3K	250	500	1K	1K	5K
5.0															
8.2															
10															
12															
15															
18															
22															
27															
33															
39															
47															
56															
68															
82															
100															
120															
150															
180															
220															
270															
330															
390															
470															
560															
680															
820															
0.001μF															
0.0012															
0.0015															
0.0018															
0.0022															
0.0027															
0.0033															
0.0039															
0.0047															
0.0056															
0.0068															
0.0082															
0.01μF															
0.012															
0.015															
0.018															
0.022															
0.027															
0.033															
0.039															
0.047															
0.056															
0.068															
0.1μF															
0.12															
0.15															
0.22															

X7R LOW VOLTAGE VALUES AND SIZES (mm)

EIA Case Size	0805		1206		1210		1812		1825		2220		2225	
Length (L)	2.00 ± 0.2		3.20 ± 0.3		3.20 ± 0.3		4.60 ± 0.3		4.60 ± 0.3		5.70 ± 0.4		5.70 ± 0.4	
Width (W)	1.25 ± 0.25		1.60 ± 0.2		2.50 ± 0.2		3.20 ± 0.3		6.35 ± 0.4		5.00 ± 0.4		6.35 ± 0.4	
Thickness max. (T)	1.45 max.		1.80 max.		2.60 max.		3.00 max.		2.60 max.		3.00 max.		3.00 max.	
Termination Width (P)	0.20 min.		0.30 min.		0.30 min.		0.30 min.		0.30 min.		0.30 min.		0.30 min.	
Capacitance	Working Voltage (Vdc)													
	50	100	50	100	50	100	50	100	50	100	50	100	50	100
0.1µF														
0.15														
0.22														
0.33														
0.47														
0.68														
1.0µF														
1.5														
2.2														
3.3														
4.7														
6.8														
10µF														

X7R HIGH VOLTAGE VALUES AND SIZES (mm)

EIA Case Size	0805			1206					1210			
Length (L)	2.00 ± 0.2			3.20 ± 0.3					3.20 ± 0.3			
Width (W)	1.25 ± 0.25			1.60 ± 0.2					2.50 ± 0.2			
Thickness max. (T)	1.45 max.			1.80 max.					2.60 max.			
Termination Width (P)	0.20 min.			0.30 min.					0.30 min.			
Capacitance	Working Voltage (Vdc)											
	200	250	500	200	250	500	630	1K	200	250	500	1K
180pF												
220												
270												
330												
390												
470												
560												
680												
0.001µF												
0.0015µF												
0.0022µF												
0.0027µF												
0.0033µF												
0.0039µF												
0.0047µF												
0.0056µF												
0.0068µF												
0.01µF												
0.012µF												
0.015µF												
0.018µF												
0.022µF												
0.027µF												
0.033µF												
0.039µF												
0.047µF												
0.056µF												
0.068µF												
0.1µF												
0.12µF												
0.15µF												
0.18µF												
0.22µF												



[illegible]