



## Short Form Data Sheet

Part number scheme

**PS KD 200 N 16 KNX**

1 2 3 4 5 6

- 1) Power Semiconductors initials
- 2) Circuit designation
- 3) Series number
- 4) Designates standard recovery time
- 5) Voltage Multiplier (example: 16 x 100 = 1600)
- 6) Proprietary suffix

### Features:

- ✓ All diffused silicone.
- ✓ Thick copper base plate.
- ✓ Isolated cooling, rated up to 3500  $V_{RMS}$
- ✓ Heat sink grounded.

MD circuit diagram



## Voltage

Parameter	Symbol	Rating	Units
Maximum Repetitive Reverse Voltage <small>Notes: 1, 3, 4, 5, 6</small>	$V_{RRM}$	1200 ~ 1800	Volts
Maximum non repetitive Surge of Reverse Voltage <small>Notes: 2, 3, 4, 5, 6</small>	$V_{RSM}$	$V_{RRM} + 100$	Volts
Maximum Non Repetitive Forward Voltage <small>Notes: 2</small>	$V_{FM} @ I_{FM}$	1.4 @ 500	V @ A
<small>Note 1: <math>T_J</math> 25°C. Note 2: <math>T_J</math> 125°C. Note 3: Measured at the peak of the sine wave, Note 6: <math>V_{RR}</math> has typical <math>I_{DR}</math>, <math>I_{RR}</math> of 2~7mA. Note 4: Below 0°C derate <math>V_{RRM}</math> 10%. Note 5: <math>V_{RRM}</math> have <math>I_{RRM}</math> of up to 20mA. Note 7: For DC applications derate <math>V_{RRM}</math> 45%.</small>			
Specifying voltage:			
1400V, PSMD200N14		1800V, PSMD200N18	
1200V, PSMD200N12		Above 1800V inquire for availability.	

## Amperage

Parameter	Symbol	Rating	Units
Maximum, Average Current <small>Notes: 3, 4</small>	$I_{F(AVE)}$	200	Amperes
Maximum, RMS Current <small>Notes: 3, 4</small>	$I_{F(RMS)}$	314	Amperes
Maximum non repetitive Surge Current with no reverse voltage reappplied. <small>Notes: 2, 4</small>	$I_{FSM} 0\% V_{RRM}$	4	kA
$I_{RR}$ = Typical Repetitive, Reverse, Current. <small>Note: 1</small>	$I_{RR}$	3 ~ 7	mA
$I_{RRM}$ = Maximum (threshold), Repetitive, Reverse, Current. <small>Note: 1</small>	$I_{RRM}$	30	mA
Fuse's absolute maximum $I^2 t$ with no reverse voltage reappplied <small>Note: 2, 4</small>	$I^2 t, 0\% V_{RR}$	5.8	kA
Fuse's absolute maximum $I^2 t$ with 100% reverse voltage reappplied <small>Note: 2, 4</small>	$I^2 t, 100\% V_{RR}$	4.1	kA
<small>Note 1: <math>T_J</math> 25°C. Note 2: <math>T_J</math> 125°C. Note 3: <math>T_{CASE}</math> 55°C air cooled. Note 4: 180°C conduction, 60Hz sine wave.</small>			

## Thermal & Weight

Parameter	Symbol	Rating	Units
Operating Temperature Range	$T_J$	-40° ~ 180°	°Celsius
Maximum Thermal resistance, Junction to Case <small>Notes: 1, 2</small>	$R_{th-J-C}$	0.15	°C/W
Maximum Thermal resistance, Case to Heat Sink <small>Notes: 1, 2</small>	$R_{th-C-HS}$	0.1	°C/W
Weight		380	Grams
		14.4	oz.
<small>Note 1: Mounting surfaces flat and greased. Note 2: 180°C conduction, 60Hz sine wave.</small>			