



## VRLA Rechargeable Battery

# BP2.3-12 (BP2.3-12FR)



### FEATURES

- Maintenance free(no water topping-up required).
- No free acid(Non-spillable battery).
- Low self-discharge rate, lower than 3% capacity loss per month.
- Can be used in any orientation(excluding used inverted).
- Absorbent Glass Mat technology for efficient gas recombination.

### APPLICATION

- UPS
- Video Camcorders



### SPECIFICATIONS

Nominal Voltage	12 V
Nominal Capacity	2.30Ah @ 20 hour rate F.V.(1.75V/cell)
Approx. Weight	940g(2.07lbs.)
Terminals	T1 (Faston Tab 187)
Internal Resistance	≤60mΩ (Fully Charged )
Max. Discharge Current	34.5 A (5 sec.)
Max. Charge Current	0.69 A
Operating Temperature Range	Charge : 0°C~40°C(32°F~104°F) Discharge : -20°C~50°C(-4°F~122°F) Storage. : -20°C~40°C(-4°F~104°F)
Container Material	ABS(UL94-HB, UL94-V0 is optional)

ISO 9001	
ISO14001	
UL	
CE	
<ul style="list-style-type: none"> <li>● IEC 61056-1</li> <li>● JIS C 8702-1</li> <li>● GB/T 19639.1</li> <li>● VdS G103025</li> </ul>	

DIMENSION(mm/inch)	OUTER DIMENSIONS	TERMINAL TYPE
<ul style="list-style-type: none"> <li>■ <b>Length</b> 178±1.5 (7.01±0.06)</li> <li>■ <b>Width</b> 34±1.5 (1.34±0.06)</li> <li>■ <b>Container Height</b> 60±1.5 (2.36±0.06)</li> <li>■ <b>Total Height</b> 65±2.0 (2.56±0.08)</li> </ul>		<ul style="list-style-type: none"> <li>● Terminal T1</li> </ul>

### Constant power discharge characteristics at 25 °C/77 °F Unit: W

Discharge Time F.V. (V/cell)	5 Min	10 Min	15 Min	30 Min	1 Hr	3 Hr	5 Hr	10 Hr	20 Hr
1.80V	83.16	61.22	49.06	29.19	16.74	6.70	4.622	2.583	1.359
1.75V	96.25	66.32	51.31	30.30	17.24	6.84	4.692	2.622	1.380
1.70V	102.26	68.70	52.90	30.99	17.55	6.90	4.718	2.635	1.392
1.65V	106.86	70.35	54.12	31.43	17.76	6.95	4.734	2.643	1.392
1.60V	110.40	71.76	55.20	31.74	17.94	6.99	4.748	2.643	1.392

### Constant current discharge characteristics at 25 °C/77 °F Unit: A

Discharge Time F.V. (V/cell)	5 Min	10 Min	15 Min	30 Min	1 Hr	3 Hr	5 Hr	10 Hr	20 Hr
1.80V	7.49	5.39	4.27	2.474	1.407	0.559	0.385	0.215	0.113
1.75V	8.83	5.84	4.46	2.568	1.449	0.570	0.391	0.218	0.115
1.70V	9.38	6.05	4.60	2.626	1.475	0.575	0.393	0.220	0.116
1.65V	9.80	6.19	4.71	2.663	1.493	0.579	0.395	0.220	0.116
1.60V	10.13	6.32	4.80	2.690	1.508	0.582	0.396	0.220	0.116

All data shall be changed without prior notice, BB reserves the right to explain and update the information contained hereinto.