





Insulated Gate Bipolar Power Transistor

- High Input Impedance
- High Peak Current Capability
- Low Gate Drive
- Strobe Flash Applications
- RoHS-compliant, halogen-free package



| | |
|----------|------|
| V_{CE} | 400V |
| I_{CP} | 150A |



Absolute Maximum Ratings

| Symbol | Parameter | Rating | Units |
|-----------------------------------|----------------------------|------------|-------|
| V_{CE} | Collector-Emitter Voltage | 400 | V |
| V_{GEP} | Peak Gate-Emitter Voltage | ±6 | V |
| I_{CP} | Pulsed Collector Current | 150 | A |
| P_D at $T_A=25^\circ\text{C}^1$ | Maximum Power Dissipation | 1 | W |
| T_{STG} | Storage Temperature Range | -55 to 150 | °C |
| T_J | Junction Temperature Range | -55 to 150 | °C |

Electrical Specifications at $T_J=25^\circ\text{C}$ (unless otherwise specified)

| Symbol | Parameter | Test Conditions | Min. | Typ. | Max. | Units |
|---------------|--------------------------------------|--|------|------|------|-------|
| I_{GE} | Gate-Emitter Leakage Current | $V_{GE}=\pm 6\text{V}$, $V_{CE}=0\text{V}$ | - | - | ±10 | uA |
| I_{CES} | Collector-Emitter Leakage Current | $V_{CE}=400\text{V}$, $V_{GE}=0\text{V}$ | - | - | 10 | uA |
| $V_{CE(sat)}$ | Collector-Emitter Saturation Voltage | $V_{GE}=2.5\text{V}$, $I_{CP}=150\text{A}$ (Pulsed) | - | 5.5 | 9 | V |
| $V_{GE(th)}$ | Gate Threshold Voltage | $V_{CE}=V_{GE}$, $I_C=250\text{uA}$ | 0.3 | - | 1.2 | V |
| Q_g | Total Gate Charge | $I_C=40\text{A}$ | - | 76 | 130 | nC |
| Q_{ge} | Gate-Emitter Charge | $V_{CE}=200\text{V}$ | - | 4 | - | nC |
| Q_{gc} | Gate-Collector Charge | $V_{GE}=4\text{V}$ | - | 26 | - | nC |
| $t_{d(on)}$ | Turn-on Delay Time | $V_{CC}=320\text{V}$ | - | 220 | - | ns |
| t_r | Rise Time | $I_C=160\text{A}$ | - | 800 | - | ns |
| $t_{d(off)}$ | Turn-off Delay Time | $R_G=10\Omega$ | - | 1.6 | - | µs |
| t_f | Fall Time | $V_{GE}=4\text{V}$ | - | 1.5 | - | µs |
| C_{ies} | Input Capacitance | $V_{GE}=0\text{V}$ | - | 4485 | 8240 | pF |
| C_{oes} | Output Capacitance | $V_{CE}=30\text{V}$ | - | 44 | - | pF |
| C_{res} | Reverse Transfer Capacitance | $f=1.0\text{MHz}$ | - | 40 | - | pF |
| R_{thJA}^1 | Thermal Resistance Junction-Ambient | | - | - | 125 | °C/W |

Notes:

1.Surface mounted on 1 in² copper pad of FR4 board

Ordering Information

AP28G45GEO-HF-3TR : in RoHS-compliant halogen-free TSSOP-8 shipped on tape and reel (3000 pcs/reel)



Typical Electrical Characteristics




Fig 1. Typical Output Characteristics




Fig 2. Typical Output Characteristics




Fig 3. Typical Saturation Voltage Characteristics




Fig 4. Collector-Emitter Saturation Voltage vs. Junction Temperature




Fig 5. Collector Current vs. Gate-Emitter Voltage




Fig 6. Collector Current vs. Gate-Emitter Voltage



Typical Electrical Characteristics (cont.)




Fig 7. Typical Capacitance Characteristics




Fig 8. Maximum Pulse Collector Current




Fig 9. Switching Time Test Circuit




Fig 10. Switching Time Waveform




Fig 11. Gate Charge Test Circuit






Fig 12. Gate Charge Waveform



Package Dimensions: TSSOP-8




| SYMBOLS | Millimeters | | |
|---------|-------------|-------|------|
| | MIN | NOM | MAX |
| A | --- | --- | 1.20 |
| A1 | 0.05 | --- | 0.15 |
| B | 0.19 | --- | 0.30 |
| C | --- | 0.127 | ---- |
| D | 2.90 | 3.00 | 3.10 |
| E | 6.20 | 6.40 | 6.60 |
| E1 | 4.30 | 4.40 | 4.50 |
| L | 0.45 | 0.60 | 0.75 |
| e | 0.65 REF. | | |
| θ | 0° | ---- | 8° |



1. All dimensions are in millimeters.
2. Dimensions do not include mold protrusions.

Marking Information:



Product: AP28G45
 28G45GEO ← GEO = RoHS-compliant TSSOP-8 with Gate ESD protection
 YWWSSS ← YWWSSS = Date/lot code
 YWW = Year and work week of manufacture.
 SSS = Lot code information.