

# MPM-15CM Series

## Chassis Mount, 15W Single, Dual & Triple Out AC/DC Power Supplies



### Key Features:

- 15W Output Power
- Universal 85-265 VAC Input
- EN 60950 Approved (UL)
- Single, Dual & Triple Outputs
- Meets EN 55022 B
- Meets IEC Safety Class II
- Chassis Mount Case

PCB Mount Models  
& DIN Rail Mount  
Option Available!



### MicroPower Direct

292 Page Street  
Suite D  
Stoughton, MA 02072  
USA

T: (781) 344-8226  
F: (781) 344-8481  
E: sales@micropowerdirect.com  
W: www.micropowerdirect.com



### Electrical Specifications

Specifications typical @ +25°C, 230 VAC input voltage & rated output current, unless otherwise noted. Specifications subject to change without notice.

#### Input

Parameter	Conditions	Min.	Typ.	Max.	Units
Input Voltage Range		85		265	VAC
Input Frequency		47		440	Hz
Input Current	See Model Selection Guide				
Inrush Current	115 VAC		15.0		A Pk
	230 VAC		30.0		
EMI	Meets CISPR Pub. 22/FCC Class B				

#### Output

Parameter	Conditions	Min.	Typ.	Max.	Units
Output Voltage	See Model Selection Guide				
Output Current	See Model Selection Guide				
Output Voltage Accuracy			±1.0	±2.0	%
Line Regulation	V <sub>IN</sub> = Min to Max		±0.2	±1.0	%
Load Regulation, Single Output	I <sub>O</sub> = Min to Max		±0.5	±1.0	%
Load Regulation, Dual, Triple Aux Output	I <sub>O</sub> = Min to Max		±2.5	±5.0	%
Ripple & Noise (20 MHz)	5.0 VDC Output		1.5	1.8	%V <sub>P-P</sub> of V <sub>O</sub>
	All Other Outputs		0.8	1.0	
Hold-Up Time	115 VAC, 60 Hz		20		mSec
Temperature Coefficient			±0.02		%/°C
Over Voltage Protection	Zener Diode Clamp		120		% of V <sub>O</sub>
Short Circuit Protection, Note 3	Continuous (Autorecovery)				
Overload Protection, Note 4	Typ. 120% to 180% of Output Power				

#### General

Parameter	Conditions	Min.	Typ.	Max.	Units
Isolation Voltage	Input to Output	3,000			VAC
Isolation Test Voltage	Input to Output, Flash Tested For 60S	4,700			VAC
Isolation Resistance	500 VDC	100			MΩ
EMI/RFI	Conducted	EN 55022 Level B			
	Electrostatic Discharge (ESD)	EN 61000-4-2 Level B			
	RF Field Susceptibility	EN 61000-4-3			
EMC Compliance	Electrical Fast Transients/Bursts On Mains	EN 61000-4-4 Level 3 2 kV			
	Surge	EN 61000-4-5 Level 3 1kV/2 kV			
Switching Frequency		100			kHz

#### Environmental

Parameter	Conditions	Min.	Typ.	Max.	Units
Operating Temperature Range	Ambient	-25	+25	+71	°C
Storage Temperature Range		-40		+85	°C
Cooling	Free Air Convection (See Derating Curve)				
Humidity	RH, Non-condensing			95	%

#### Physical

Case Size, Chassis Mount	3.81 x 2.13 x 0.92 Inches (96.7 x 54.0 x 23.3 mm)
Case Size, DIN Rail Option	3.81 x 2.13 x 1.35 Inches (96.7 x 54.0 x 34.3 mm)
Case Material	Non-Conductive Plastic & Fiberglass (UL94-V0)
Weight	5.69 Oz (162g)

#### Reliability Specifications

Parameter	Conditions	Min.	Typ.	Max.	Units
MTBF	MIL HDBK 217F, 25°C, Gnd Benign	280			kHours
Safety Standards	UL 60950, EN 60950				
Safety Approvals	UL, cUL; File No. E245422				
Safety Class	IEC 61140 Class II				

[www.micropowerdirect.com](http://www.micropowerdirect.com)


Model Number	Input		Output 1 (Vout 1)			Output 2 (Vout 2)			Output 3 (Vout 3)			Capacitive Load (µF, Max)	Efficiency (% Typ)
	Current (A)		Voltage (VDC)	Current (A)		Voltage (VDC)	Current (A)		Voltage (VDC)	Current (A)			
	115 VAC	230 VAC		Max.	Min.		Max.	Min.		Max.	Min.		
MPM-15S-05CM	0.290	0.14	5.0	3.000	0.300							3,900	75
MPM-15S-12CM	0.275	0.14	12.0	1.250	0.125							2,200	79
MPM-15S-15CM	0.275	0.14	15.0	1.000	0.100							2,200	79
MPM-15S-24CM	0.275	0.14	24.0	0.625	0.063							2,200	79
MPM-15S-48CM	0.273	0.14	48.0	0.310	0.030							1,000	79
MPM-15D-12CM	0.275	0.14	+12.0	+0.625	+0.063	-12.0	-0.625	-0.063				±1,500	79
MPM-15D-15CM	0.275	0.14	+15.0	+0.500	+0.050	-15.0	-0.500	-0.050				±1,500	79
MPM-15T-0512CM	0.290	0.14	5.0	2.000	+0.200	+12.0	+0.200	+0.020	-12.0	-0.200	-0.020	Note 5	74
MPM-15T-0515CM	0.284	0.14	5.0	1.80	+0.200	+15.0	+0.150	+0.015	-15.0	-0.150	-0.015	Note 5	74

Other output combinations are available  
Contact the factory for details at:  
sales@micropowerdirect.com

Notes:

1. Load regulation is measured for an output change of 0% to 100% at nominal input line. For multiple output models, the loads are balanced.
2. Operation at no-load will not damage these units. However, they may not meet all specifications.
3. Output short circuit protection is provided by a "hiccup mode" circuit. The unit recovers automatically when the fault condition is removed.
4. Output overload protection is provided by a fold back current limiting circuit.
5. For triple output models, the maximum capacitive load for 5 VDC outputs is 2,200 µF. For all other outputs it is ±1,500 µF.
6. The **MPM-15CM** series includes a built-in 2.0A/250 VAC fuse. It is recommended that an external 1.5A slow blow fuse also be used on the input for protection.

Derating Curve




Pin Connections

Pin	Single	Dual	Triple
1		AC-Neutral	
2		AC-Line	
3	NC	NC	-Vo 3
4	-Vo	-Vo	Common 2/3
5	NC	Common	+Vo 2
6	+Vo	+Vo	-Vo 1
7	NC	NC	+Vo 1

NC = No Connection

Mechanical Dimensions, Chassis Mount



Model Number  
**MPM15X-YYCM**

Outputs  
S = Single  
D = Dual  
T = Triple

Output Voltage Selection  
(i.e. 05 = 5 VDC, 24 = 24 VDC, etc)

Mounting Type  
CM = Chassis Mount

A DIN Rail mounting kit is available  
Contact the factory for details at:  
sales@micropowerdirect.com

Notes:

- All dimensions are typical in inches (mm)
- Tolerance x.xx = ±0.01 (±0.25)



**MicroPower Direct**  
**We Power Your Success - For Less!**