

IS5300

324-port 40Gb/s InfiniBand Chassis Switch

The IS5300 switch provides the highest performing fabric solution by delivering high bandwidth and low-latency to Enterprise Data Centers and High-Performance Computing environments in a 16U chassis. Networks built with the IS5300 can carry converged traffic with the combination of assured bandwidth and granular quality of service.

World Class Modularity and Next Generation Scalability

Built with Mellanox's 4th generation InfiniScale® InfiniBand switch device, the IS5300 provides full bisectional bandwidth up to 40Gb/s per port. With up to 324 QSFP ports, this system is among the densest switching systems available. The IS5300 supports a superior scalable platform that scales as the number of nodes per cluster and the number of cores per node increases. This modular chassis switch is an ideal choice for building medium to large size clusters or for use as a core switch for large clusters.

Efficient Computing and Scalable I/O Consolidation

The IS5300 supports adaptive routing as well as static routing to reduce or eliminate congestion situations. Hardware-based adaptive routing dynamically and automatically re-routes traffic to alleviate congested ports and dynamically adjusts the network in real time. The granular Quality of Service (QoS) integrated into the IS5300 enables I/O consolidation over InfiniBand and provides efficient network management mechanisms for LAN and SAN protocols.

Whether used for parallel computation or as a converged fabric, the combination of high bandwidth, adaptive routing, congestion control and granular QoS provide the industry's best traffic carrying capacity.

High Availability


The IS5300 delivers director-class availability required for mission-critical application environments. The leaf, spine blades and management modules as well as the power supplies and fan units are all hot-swappable to help eliminate down time.

Management Capabilities

The IS5300 comes with an onboard subnet manager, enabling simple, out-of-the-box fabric bring up for up to 648 nodes.

FabricIT™ fabric management running on the IS5300 enables fast setup for cluster bring-up, fabric-wide bandwidth and latency verification, diagnostic tools and cluster topology view.

FabricIT™ chassis management is embedded in the IS5300 and provides administrative tools to manage the firmware, power supplies, fans, ports, and other interfaces.



IS5300

HIGHLIGHTS

BENEFITS

- Industry-leading, switch platform in performance, power and density
- Unlimited scalability across storage, application and database servers
- High-bandwidth, low-latency fabric for compute-intensive applications

KEY FEATURES

- 324 QDR (40Gb/s) QSFP ports
- 25.92Tb/s switching capacity
- 100ns to 300ns switching latency
- Hardware-based routing
- Congestion control
- Quality of Service enforcement

MANAGEMENT

- Fast and efficient fabric bring-up
- Comprehensive chassis management
- Intuitive CLI and GUI for easy access

HARDWARE

INFINIBAND SWITCH

- 19" rack mountable chassis, 16U* height
- Up to 324 QDR (40 Gb/s) QSFP ports
- Aggregate data throughput of 25.92 Tb/s
- 100ns to 300ns port-to-port latency
- IBTA 1.21 compliant
- Adaptive routing
- congestion control
- Port mirroring
- 48K entry linear forwarding data base
- 4K entry multicast forwarding data base

CONNECTORS AND CABLING

- QSFP connectors
- Passive/Active copper or fiber cable
- Fiber media adapters

INDICATORS

- Per port status LEDs: Link, Activity
- System status LEDs:
System, thermal, voltages, fans

POWER SUPPLY

- 1KW 48VDC hot-swappable units
- Two additional slots for optional redundancy
- Input range: 90-264VAC
- Frequency: 47-63Hz, single phase AC

COOLING

- Hot-swappable fan trays
- Front-to-rear air flow
- Auto-heat sensing

COMPLIANCE

SAFETY

- US/Canada: cTUVus
- EU: IEC60950
- International: CB

EMC (EMISSIONS)

- USA: FCC, Class A
- Canada: ICES, Class A
- EU: EN55022, Class A
- EU: EN55024, Class A
- EU: EN61000-3-2, Class A
- EU: EN61000-3-3, Class A
- Japan: VCCI, Class A

ENVIRONMENTAL

- EU: IEC 60068-2-64: Random Vibration
- EU: IEC 60068-2-29: Shocks, Type I / II
- EU: IEC 60068-2-32: Fall Test

ACOUSTIC

- ISO 7779
- ETS 300 753

OPERATING CONDITIONS

- Operating temperature: 10 to 45° C
- Humidity: 10-90% non-condensing

OTHERS

- RoHS-5 compliant
- 1-year warranty

*Shelf will add 1U

Ordering Part Number	Description
MIS5300D-6DNC	InfiniScale IV, 12.96Tb/s DDR InfiniBand Chassis Switch, 18 Leaf Slots, Managed
MIS5300Q-6DNC	InfiniScale IV, 25.92Tb/s QDR InfiniBand Chassis Switch, 18 Leaf Slots, Managed
MIS5001DC	InfiniScale IV, 18 + 18 port QSFP DDR 20Gb/s InfiniBand Leaf Blade
MIS5001QC	InfiniScale IV, 18 + 18 port QSFP QDR 40Gb/s InfiniBand Leaf Blade
MIS5600MDC	PowerPC460 Management Module

Please visit Mellanox's web site for more cable information, best usage practice and availability.



350 Oakmead Parkway, Suite 100, Sunnyvale, CA 94085
Tel: 408-970-3400 • Fax: 408-970-3403
www.mellanox.com