

10-31-01



1. ALL DIMS ARE IN INCHES (MILLIMETERS).
2. TOLERANCE IS $\pm 0.010"$ ($\pm 0.25\text{mm}$) UNLESS OTHERWISE SPECIFIED.
3. LEAD SPACING IS MEASURED WHERE LEADS EMERGE FROM THE PACKAGE.
4. SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.
5. LEADS TO BE SOLDERABLE AND CAPABLE OF MEETING THE SOLDERABILITY REQUIREMENTS OF MIL-STD-202, METHOD 208.
6. MANUFACTURE DATE SHALL NOT BE OLDER THAN 26 WEEKS (6 MONTHS).

WARNING: DO NOT LOOK AT LED DIRECTLY WHEN POWER IS ON, USE IR CAMERA TO VIEW LED

40

LEAD SOLDERING TEMP: [1.6mm (.063In) FROM BODY] 240°C FOR 5 SEC.

23105 KASHIWA COURT
TORRANCE, CA 90505

-PROPRIETARY-
This document contains Proprietary
Information of LEDTRONICS, INC.
It may not be copied, used or disclosed
for any purpose without the prior express
written consent of LEDTRONICS, INC.

**XOX ± .010 TOLERANCE PER ANSI-Y14.5
.XX ± .025 (UNLESS OTHERWISE STATED)**
ANGLES ± 0°.30"
FRACT. ± 1/32

CUSTOMER