



UNCONTROLLED DOCUMENT









PART NUMBER	SSL-LX4673USBD-LA20	REV.	В
DATE	E.C.N. NUMBER AND REVISION COMMENTS		REV.
07.10.01	E.C.N. #10BRDR. & REDRAWN IN 3D.		Α
08.17.12	E.C.N. #10BRDR. & REDRAWN.		В

ELECTRO-OPTICAL	CHARACTERISTICS Ta=25°C	If=20mA			
PARAMETER	MIN	TYP	MAX	UNITS	TEST COND
PEAK WAVELENGTH		470		nm	
FORWARD VOLTAGE		3.5	4.0	Vf	
REVERSE VOLTAGE	5.0			Vr	امبر100 Ir=100
AXIAL INTENSITY		60		mcd	If=20mA
VIEWING ANGLE		100		2x theta	
EMITTED COLOR:	BLUE				
LENS FINISH:	BLUE DIFFUSED				

2TIMI I	ΩF	SAFF	OPERATION	AΤ	25°C	

PARAMETER	MAX	UNITS
PEAK FORWARD CURRENT*	100	mA
STEADY CURRENT	30	mA
POWER DISSIPATION	98	mW
DERATE FROM 25°C	-1.2	mW/*C
OPERATING TEMP.	-40 TO +85	•c
STORAGE TEMP.	-40 TO +85	•c
SOLDERING TEMP.	+260	*C
2.0mm FROM BODY	3	SEC.
* +<10uC		

t<10µS

CAUTION: STATIC SENSITIVE DEVICE FOLLOW PROPER E.S.D. HANDLING PROCEDURES WHEN WORKING WITH THIS PART.

—5.65 [0.222]—

1.50 [0.059]

2.54 [0.100]

3.15 [0.124]

CATHODE A

0.50 [0.020] SQR. (2 PLS.)

*UNLESS OTHERWISE SPECIFIED TOLERANCES PER DECIMAL PRECISION ARE: X=±1 (±0.039), X.X=±0.5 (±0.020), X.XX=±0.25 (±0.010), X.XXX=±0.127 (±0.005). LEAD SIZE=±0.05 (±0.002), LEAD LENGTH=±0.75 (±0.030). MIN= +DECIMAL PRECISION MAX.= +0.00 (±0.002), X.XX=±0.127 (±0.005).

QUASARBRITE 4mm x 7mm RECT LED, 470nm BLUE, BLUE DIFFUSED.

THE SPECIFICATIONS MAY CHANGE AT ANY TIME WITHOUT NOTICE DUE TO NEW MATERIALS OR PRODUCT IMPROVEMENT.

CONFIDENTIAL INFORMATION
THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX INC., THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES.

UNCONTROLLED DOCUMENT DATE: 08.17.12 DRAWN BY: AΒ PAGE: 1 OF 1 CHKD BY: KF SCALE: NTS APRVD BY: KF (Pg) UNIT: mm [INCH]

Greating LED and LCD Solutions Together "

E. HELEN ROAD ATINE, IL 60067-6976 ONE: +1.847.359.2790 +1.847.359.6538 : WWW.LUMEX.COM MEMBER OF ITW PHOTONICS GROUP