



UNCONTROLLED DOCUMENT




LEAD FREE REFLOW PROFILE



TOTAL TIME ABOVE 220°C IS 60 SECONDS MAX.

RECOMMENDED SOLDER PAD LAYOUT



CAUTION: MOISTURE SENSITIVE DEVICE

1. SHELF LIFE IN SEALED BAG:
12 MONTHS AT <40°C AND <90% RELATIVE HUMIDITY (RH).

2. AFTER THIS BAG IS OPENED, DEVICES HAVE TO BE MOUNTED WITHIN 48 HOURS OR STORED AT <30% RH.

CAUTION: STATIC SENSITIVE DEVICE

FOLLOW PROPER E.S.D. HANDLING PROCEDURES WHEN WORKING WITH THIS PART.

ELECTRO-OPTICAL CHARACTERISTICS @ 25°C OF PIN PHOTODIODE						
PARAMETER	SYM	MIN	TYP	MAX	UNITS	TEST COND.
REVERSE BREAKDOWN VOLTAGE	V_{BR}	32	170	-	V	$I_R=100\mu A$
SPECTRAL BANDWIDTH	$\lambda_{0.5}$	-	730-1200	-	nm	
PEAK WAVELENGTH	λ_P	-	980	-	nm	
TOTAL CAPACITANCE	C_t	-	6	-	pF	(4)
OPEN CIRCUIT VOLTAGE	V_o	-	410	-	mV	(1)
SHORT CIRCUIT CURRENT	I_{sc}	-	15	-	μA	(1)
REVERSE DARK CURRENT	I_R	-	-	10	nA	(2)
TURN ON/OFF TIME	ON/OFF	-	10	-	ns	(3)

- (1) $C_T=2870^\circ K$; $H=5mW/cm^2$
- (2) $V_R=10V$; $H=0mW/cm^2$
- (3) $V_R=10V$; $R_L=1000\Omega$
- (4) $E_e = 0mW/cm^2$; $F=1MHz$; $V=10V$

LIMITS OF SAFE OPERATION AT 25°C		
PARAMETER	MAX	UNITS
POWER DISSIPATION	150	mW
REVERSE VOLTAGE	32	V
DERATE FROM 25°C	-1.2	mW/°C
OPERATING TEMP.	-25 TO +85	°C
STORAGE TEMP.	-30 TO +85	°C

NOTES:

1. LENS TO HAVE DAYLIGHT FILTER.
2. 2,000 PIECES PER REEL.
3. MOISTURE SENSITIVE LABEL ON REEL AND BAG.
4. ANTISTATIC HEATSEALED BAG.

UNCONTROLLED DOCUMENT

REV.

C

PART NUMBER

OED-HPI1210B-60A

SMT PHOTODIODE, 1210 PACKAGE,
60mil x 60mil CHIP, WITH DAYLIGHT FILTER.

CONFIDENTIAL INFORMATION

THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX INC., THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES.

RELIABILITY NOTE

OUR MANY YEARS OF EXPERIENCE DATA ACCUMULATION INDICATE THAT SOLDER HEAT IS A MAJOR CAUSE OF EARLY AND FUTURE FAILURE. PLEASE PAY ATTENTION TO YOUR SOLDERING PROCESS.



290 E. HELEN ROAD
PALATINE, IL 60067-6976
PHONE: +1.847.359.2790
US WEB: www.lumex.com
TW WEB: www.lumex.com.tw

DRAWN BY:

GB

CHECKED BY:

APPROVED BY:

DATE: 9.20.02

PAGE: 1 OF 1

SCALE: N/A