ALPHA & OMEGA SEMICONDUCTOR

AON2707

30V P-Channel MOSFET with Schottky Diode

General Description

The AON2707 uses advanced trench technology to provide excellent $R_{DS(ON)}$ and low gate charge. A Schottky diode is provided to facilitate the implementation of a bidirectional blocking switch, or for DC-DC conversion applications.

Product Summary

V_{DS}	-30V
I_D (at V_{GS}=-10V)	-4A
$R_{DS(ON)}$ (at V_{GS}=-10V)	< 117mΩ
$R_{DS(ON)}$ (at V_{GS}=-4.5V)	< 138mΩ
$R_{DS(ON)}$ (at V_{GS}=-2.5V)	< 193mΩ
Typical ESD protection	**HBM Class 2**
V_{KA}	20V
I_F	2A
V_F (at I_F=1A)	<0.45V

Green Product

DFN 2x2

Top View Bottom View





Absolute Maximum Ratings T_A=25°C unless otherwise noted

Parameter		Symbol	MOSFET	Schottky	Units
Drain-Source Voltage		V_{DS}	-30		V
Gate-Source Voltage		V_{GS}	±12		V
Continuous Drain Current [A]	T_A=25°C	I_D	-4		A
	T_A=70°C		-3		
Pulsed Drain Current [B]		I_{DM}	-15		
Schottky reverse voltage		V_{KA}		20	V
Continuous Forward Current [A]	T_A=25°C	I_F		2.5	A
	T_A=70°C			1.5	
Pulsed Forward Current [B]		I_{FM}		15	
Power Dissipation [A]	T_A=25°C	P_D	2.8	2.7	W
	T_A=70°C		1.8	1.7	
Junction and Storage Temperature Range		T_J, T_{STG}	-55 to 150	-55 to 150	°C

Thermal Characteristics

Parameter: MOSFET		Symbol	Typ	Max	Units
Maximum Junction-to-Ambient [A]	t ≤ 10s	$R_{\theta JA}$	35	45	°C/W
Maximum Junction-to-Ambient [A]	Steady-State		65	85	°C/W
Parameter: Schottky					
Maximum Junction-to-Ambient [A]	t ≤ 10s	$R_{\theta JA}$	36	47	°C/W
Maximum Junction-to-Ambient [A]	Steady-State		67	87	°C/W

Electrical Characteristics (T_J=25℃ unless otherwise noted)

Symbol	Parameter	Conditions	Min	Typ	Max	Units
STATIC PARAMETERS						
BV_{DSS}	Drain-Source Breakdown Voltage	I_D=-250µA, V_{GS}=0V	-30			V
I_{DSS}	Zero Gate Voltage Drain Current	V_{DS}=-30V, V_{GS}=0V			-1	µA
		T_J=55℃			-5	
I_{GSS}	Gate-Body leakage current	V_{DS}=0V, V_{GS}=±12V			±10	µA
$V_{GS(th)}$	Gate Threshold Voltage	V_{DS}=V_{GS}, I_D=-250µA	-0.7	-1.05	-1.5	V
$I_{D(ON)}$	On state drain current	V_{GS}=-10V, V_{DS}=-5V	-15			A
$R_{DS(ON)}$	Static Drain-Source On-Resistance	V_{GS}=-10V, I_D=-4A		97	117	mΩ
		T_J=125℃		138	165	
		V_{GS}=-4.5V, I_D=-2A		110	138	mΩ
		V_{GS}=-2.5V, I_D=-1A		148	193	mΩ
g_{FS}	Forward Transconductance	V_{DS}=-5V, I_D=-4A		9		S
V_{SD}	Diode Forward Voltage	I_S=-1A,V_{GS}=0V		-0.8	-1	V
I_S	Maximum Body-Diode Continuous Current				-3.2	A
DYNAMIC PARAMETERS						
C_{iss}	Input Capacitance	V_{GS}=0V, V_{DS}=-15V, f=1MHz		305		pF
C_{oss}	Output Capacitance			42		pF
C_{rss}	Reverse Transfer Capacitance			26		pF
R_g	Gate resistance	V_{GS}=0V, V_{DS}=0V, f=1MHz		8.5	17	Ω
SWITCHING PARAMETERS						
$Q_{g(10V)}$	Total Gate Charge	V_{GS}=-10V, V_{DS}=-15V, I_D=-4A		6.8	12	nC
$Q_{g(4.5V)}$	Total Gate Charge			3.2	6	nC
Q_{gs}	Gate Source Charge			0.75		nC
Q_{gd}	Gate Drain Charge			1.2		nC
$t_{D(on)}$	Turn-On DelayTime	V_{GS}=-10V, V_{DS}=-15V, R_L=3.75Ω, R_{GEN}=3Ω		6.0		ns
t_r	Turn-On Rise Time			5		ns
$t_{D(off)}$	Turn-Off DelayTime			21		ns
t_f	Turn-Off Fall Time			6.5		ns
t_{rr}	Body Diode Reverse Recovery Time	I_F=-4A, dI/dt=100A/µs		15		ns
Q_{rr}	Body Diode Reverse Recovery Charge	I_F=-4A, dI/dt=100A/µs		6		nC
SCHOTTKY PARAMETERS						
V_F	Forward Voltage Drop	I_F=1A		0.4	0.45	V
I_{rm}	Maximum reverse leakage current	V_R=5V			0.05	mA
		V_R=5V, T_J=125℃			10	
I_{rm}	Maximum reverse leakage current	V_R=16V			0.1	mA
		V_R=16V, T_J=125℃			20	
C_T	Junction Capacitance	V_R=10V		34		pF
t_{rr}	Schottky Reverse Recovery Time	I_F=1A, dI/dt=100A/µs		11	14	ns
Q_{rr}	Schottky Reverse Recovery Charge	I_F=1A, dI/dt=100A/µs		0.8		nC

A: The value of $R_{\theta JA}$ is measured with the device mounted on 1in ^{2} FR-4 board with 2oz. Copper, in a still air environment with T_A=25° C. The value in any given application depends on the user's specific board design. The current rating is based on the t ≤ 10s thermal resistance rating.
B: Repetitive rating, pulse width limited by junction temperature.
C. The $R_{\theta JA}$ is the sum of the thermal impedance from junction to lead $R_{\theta JL}$ and lead to ambient.
D. The static characteristics in Figures 1 to 6 are obtained using <300 ms pulses, duty cycle 0.5% max.
E. These tests are performed with the device mounted on 1 in ^{2} FR-4 board with 2oz. Copper, in a still air environment with T_A=25° C. The SOA curve provides a single pulse rating.

THIS PRODUCT HAS BEEN DESIGNED AND QUALIFIED FOR THE CONSUMER MARKET. APPLICATIONS OR USES AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS ARE NOT AUTHORIZED. AOS DOES NOT ASSUME ANY LIABILITY ARISING OUT OF SUCH APPLICATIONS OR USES OF ITS PRODUCTS. AOS RESERVES THE RIGHT TO IMPROVE PRODUCT DESIGN, FUNCTIONS AND RELIABILITY WITHOUT NOTICE.

TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS



Fig 1: On-Region Characteristics



Figure 2: Transfer Characteristics



Figure 3: On-Resistance vs. Drain Current and Gate Voltage



Figure 4: On-Resistance vs. Junction Temperature



Figure 5: On-Resistance vs. Gate-Source Voltage



Figure 6: Body-Diode Characteristics

TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS



Figure 7: Gate-Charge Characteristics



Figure 8: Capacitance Characteristics



Figure 9: Maximum Forward Biased Safe Operating Area (Note E)



Figure 10: Single Pulse Power Rating Junction-to-Ambient (Note E)



Figure 11: Normalized Maximum Transient Thermal Impedance (Note E)

TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS



Figure 12: Schottky Forward Characteristics



Figure 13: Schottky Capacitance Characteristics



Figure 14: Schottky Forward Drop vs. Junction Temperature



Figure 15: Schottky Leakage Current vs. Junction Temperature



Figure 16: Schottky Normalized Maximum Transient Thermal Impedance (Note E)

Gate Charge Test Circuit & Waveform



Resistive Switching Test Circuit & Waveforms



Diode Recovery Test Circuit & Waveforms