

1x2 1064/1550nm Fused PM Fiber Standard WDM



Product Features

- Low Excess Loss
- High Extinction Ratio
- High Power Handling
- Available for Slow or Fast Axis Operation
- Telcordia GR-1221 Compliant Test

Product Applications

- PM Fiber EDFAs
- Monitoring in Coherent Systems
- Fiber Lasers

Specifications			1064/1550nm	
Parameter	Unit		Premium	A grade
Pump Channel	nm		1064±10	
Insertion Loss	Max.	dB	0.5	0.6
Polarization Extinction ratio	Min.	dB	20	17
Isolation@ 1530 to 1565nm	Min.	dB	18	17
Signal Channel	nm		1530 to 1565	
Insertion Loss	Max.	dB	0.7	0.9
Polarization Extinction ratio	Min.	dB	20	17
Isolation@ 1064±10nm	Min.	dB	18	17
Operating power	Max.	W	2	
Operating Temperature		°C	-40 to +85	
Storage Temperature		°C	-50 to +85	
Package Type		mm	S7 / S9 / M1	

All specifications are before connectors. PER is 2dB lower and EL is 0.2dB higher after connectors.

Ordering Information

P	M	S	W			0	0					
Wavelength E=1064/1550nm S=Specify	Structure 1=1x2	Grade P=Premium A=A grade	Package 6=S7 with 250um bare fiber pigtail 8=S9 with 0.9mm loose tube D=M1 with 3mm cable	Fiber Type E=Panda fiber	Fiber Length 0=0.5m 1=0.75m 2=1.0m S=Specify	Connector 0=None 1=FC/PC 2=FC/SPC 3=FC/APC 7=FC/UPC						

Note: 1. Central Wavelength can be customized for different applications.
2. All specifications are subject to change without notice.