



JKL LAMP NUMBER	VOLTS RATED	AMPS ±10%	MSCP ±25%	LUMENS ±25%	AVERAGE LIFE HRS.
AW24	1.3	.018	.0012	.015	1,000

NOTES:

- GLASS ENVELOPE TO BE TIPLESS AND SEAMLESS CONSTRUCTION TO PROVIDE UNDISTORTED END VIEWING.
- WIRE TERMINALS TO BE TINNED DUMET TYPE WIRE. OPTIONAL PLATING MATERIALS ARE AVAILABLE.
- ALL LAMPS TO BE 100% AGED FOR AN EQUIVALENT OF TEN HOURS OF THE RATED VOLTAGES.
- FINAL INSPECTION ON ALL LAMPS TO BE PER MIL. STD. 105D TO AN AQL OF 2.6.
NOTE: AS15 TYPE LAMPS WILL BE 100% INSPECTED FOR AMPERAGE AND MSCP RATINGS.
- ALL DIMENSIONS PROVIDED HEREIN, NOT LISTING TOLERANCES, ARE CONSIDERED REFERENCE DIMENSIONS ONLY.

METRIC		DIMENSIONS ARE IN MILLIMETERS		JKL COMPONENTS CORPORATION			
THIRD ANGLE PROJECTION		TOLERANCE UNLESS OTHERWISE SPECIFIED		TITLE			
		1 PL ± 0.2		T-3/4 STANDARD WIRE TERMINAL LAMP			
		2 PL ± 0		SIZE	PCB NO.	DRAWING NO.	
		ANGLE ± 0		A	55335	AW24	
DRAWN BY		APPROV BY DATE		SCALE	RELEASED DATE	REVISION DATE	REV. NO.
L. WENGSTROM		E.D. 3/5/03		NONE	3/5/03		
RELEASED		3/5/03		- CAD DRAWING -			
				MANUAL REVISIONS NOT PERMITTED			
REV. NO.	DESCRIPTION/ECO NUMBER	APPROV DATE					SHEET 1 of 1