


JKL PART NUMBER	COLOR RGB WHITE	STARTING CIRCUIT VOLTAGE VS (Vrms)	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mA rms)	BRIGHTNESS (CANDELA/m ²)	*RATED LIFE (HRS)
BF22316-29B	x = .312 y = .307	1160 @ 0°C	725	5 ± 1	34,000 ±20%	20,000

* RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

			METRIC  THIRD ANGLE PROJECTION		DIMENSIONS ARE IN MILLIMETERS TOLERANCE UNLESS OTHERWISE SPECIFIED 1 PL +/- REF. 2 PL +/- REF. ANGLE +/- 0		JKL COMPONENTS CORPORATION				
					TITLE MINIATURE COLD CATHODE FLUORESCENT LAMP						
B	BRIGHTNESS ±20%	6/13/08	DRAWN BY	APPV'D BY	DATE	SIZE	FSCM NO.	DRAWING NO.	BF22316-29B		
A	ADD/CHNG. DIMENSIONS & ELECT. RATINGS	3/21/08	L. WENGSTROM	L.R.	6/13/08	A	55335				
	RELEASE & CANCEL P-0709-05	1/23/08				SCALE	RELEASED DATE	REVISION DATE	REV. NO.	SHEET	
REV. NO.	DESCRIPTION/ECO NUMBER	APPV'D DATE	- CAD DRAWING - MANUAL REVISIONS NOT PERMITTED			NONE	1/23/08	6/13/08	B	1 OF 1	