



JKL PART NUMBER	COLOR GREEN	LAMP WATTS	STARTING CIRCUIT VOLTAGE VS (Vrms)	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mA rms)	BRIGHTNESS (CANDELA/m ²)	*RATED LIFE (HRS)
BF3165-11B	x = 0.318 ± 0.03 x = 0.556 ± 0.03	1.8	925 @ 0°C	365	5 ± 1	38,000 TYP. 26,600 MIN.	20,000 AVG.

*NOTE: RATED LIFE IS DEFINED AS THE POINT AT WHICH THE OUTPUT BECOMES 50% OF THE INITIAL RATING.

NOTE: ALL SPECIFICATIONS ARE TYPICAL WITH THE LAMP OPERATING, AFTER STABILIZATION, AT AN AMBIENT TEMPERATURE OF 25°C.

			METRIC DIMENSIONS ARE IN MILLIMETERS TOLERANCE UNLESS OTHERWISE SPECIFIED 1 PL +/- REF. 2 PL +/- REF. ANGLE +/- 0		JKL COMPONENTS CORPORATION					
 THIRD ANGLE PROJECTION					TITLE MINIATURE 3.0 GREEN CCFL					
DRAWN BY		APPVD BY		DATE	SIZE	FSCM NO.	DRAWING NO.			
L. WENGSTROM		J.K.		3/23/05	A	55335	BF3165-11B			
- CAD DRAWING -			SCALE		RELEASED DATE	REVISION DATE	REV. NO.	SHEET		
MANUAL REVISIONS NOT PERMITTED			NONE		10/31/02	3/23/05	A	1 OF 1		
REV. NO.	DESCRIPTION/ECO NUMBER	APPVD DATE								
A	CORRECT ELECTRICAL SPECIFICATIONS PROTOTYPE RELEASE	3/23/05 10/31/02								