



JKL LAMP PART NO.	COLOR LCD HIGH OUTPUT WHITE 8800°k RGB	STARTING CIRCUIT VOLTAGE VS (Vrms) @ 0°C	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mAmps)	BRIGHTNESS (CANDELA/m2)	*RATED LIFE (HRS) AVERAGE
BF3294-24B	x = .285 y = .278	1550	620	5 ± 1	28,000 ± 10%	40,000

* RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

<p>THIRD ANGLE PROJECTION</p>	<p>METRIC</p>	<p>DIMENSIONS ARE IN MILLIMETERS</p> <p>TOLERANCE UNLESS OTHERWISE SPECIFIED</p> <p>1 PL +/- 0</p> <p>2 PL +/- 0</p> <p>ANGLE +/- 0</p>	<p>JKL COMPONENTS CORPORATION</p>						
	<p>TITLE: MINIATURE COLD CATHODE FLUORESCENT LAMP</p>								
<p>REV. NO.</p>	<p>DESCRIPTION/ECO NUMBER</p>	<p>APPV'D DATE</p>	<p>DRAWN BY</p>	<p>APPV'D BY DATE</p>	<p>SIZE</p>	<p>FSCM NO.</p>	<p>DRAWING NO.</p>	<p>REV. NO.</p>	<p>SHEET</p>
	<p>RELEASE & CANCEL P-0308-05</p>	<p>5/17/04</p>	<p>L. WENGSTROM</p>	<p>J.K. 8/5/04</p>	<p>A</p>	<p>55335</p>	<p>BF3294-24B</p>	<p>A</p>	<p>1 OF 1</p>
			<p>- CAD DRAWING -</p> <p>MANUAL REVISIONS NOT PERMITTED</p>			<p>SCALE</p>	<p>RELEASED DATE</p>	<p>REVISION DATE</p>	
						<p>NONE</p>	<p>5/17/04</p>	<p>8/5/04</p>	