


JKL PART NUMBER	COLOR (REF.)	STARTING CIRCUIT VOLTAGE VS (Vrms)	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mAmps)	BRIGHTNESS (CANDELA/m2)	*RATED LIFE (HRS)
BF4320-27B	x = .293 y = .293	@ 0° C 1300	@ 25° C 545	5 ± 1	14400	20,000

\*NOTE: RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

METRIC



THIRD ANGLE PROJECTION

DIMENSIONS ARE IN MILLIMETERS

TOLERANCE UNLESS OTHERWISE SPECIFIED

1 PL +/- 0  
2 PL +/- 0  
ANGLE +/- 0

**JKL**

COMPONENTS CORPORATION

TITLE

SINGLE LEAD TIPLESS MINIATURE  
FLUORESCENT LAMP

DRAWN BY  
L. WENGSTROM

APPV'D BY DATE  
J.K. 12/9/02

SIZE  
**A**

FSCM NO.  
**55335**

DRAWING NO.

**BF4320-27B**

RELEASED AND CANCEL P-0210-03

12/9/02

REV. NO.

DESCRIPTION/ECO NUMBER

APPV'D DATE

- CAD DRAWING -

MANUAL REVISIONS NOT PERMITTED

SCALE

NONE

RELEASED DATE

12/9/02

REVISION DATE

REV. NO.

SHEET 1 of 1