


JKL LAMP PART NUMBER	COLOR RGB WHITE	STARTING CIRCUIT VOLTAGE VS (Vrms)	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mA rms)	BRIGHTNESS Cd/m <sup>2</sup> @ 25°C	*RATED LIFE (HRS)
BF48340-39B	6,200 KELVIN x = .323 / y = .309	1,365 @ 25°C	545	5 ± 1	10,000 TYP. 7,000 MIN.	20,000 (AVG.) 10,000 (MIN.)

\* RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

NOTE: ALL SPECIFICATIONS ARE TYPICAL WITH THE LAMP OPERATING, AFTER STABILIZATION, AT AN AMBIENT TEMPERATURE OF 25°C.

<b>METRIC</b>  THIRD ANGLE PROJECTION	DIMENSIONS ARE IN MILLIMETERS TOLERANCE UNLESS OTHERWISE SPECIFIED 1 PL +/- 0 2 PL +/- 0 ANGLE +/- 0	<b>JKL COMPONENTS CORPORATION</b>				
		TITLE <b>MINIATURE COLD CATHODE          FLUORESCENT LAMP</b>				
DRAWN BY L. WENGSTROM	APPVD BY J.K.	DATE 3/15/05	SIZE <b>A</b>	FSCM NO. <b>55335</b>	DRAWING NO. <b>BF48340-39B</b>	
- CAD DRAWING - MANUAL REVISIONS NOT PERMITTED		SCALE NONE	RELEASED DATE 3/15/05	REVISION DATE	REV. NO.	SHEET 1 OF 1

RELEASE & CANCEL P-0412-06	3/15/05
REV. NO.	DESCRIPTION/ECO NUMBER
	APPVD DATE