



V1 FILAMENT:
 5.2-5.5 VDC
FILAMENT CURRENT:
 45 +/- 10 mA DC
V2 ELECTRODE SOURCE:
 24-26 VDC TYP.
ELECTRODE CURRENT:
 14 +/- 3.0 mA DC
BALLAST RESISTOR:
 1K TYP.
ELECTRODE RUNNING VOLTAGE:
 10 +/- 3.0 V DC
TOTAL LAMP WATTAGE:
 .40 TYP.
INTENSITY
 .1mW/Cm2 @ 351nm (REF.)
LIFE HOURS:
 *10,000

*TO 50% OUTPUT INTENSITY

NOTE: CLEAR GLASS

JKL PART NO.: BGF717-UV351

	METRIC	DIMENSIONS ARE IN MILLIMETERS		COMPONENTS CORPORATION			
	THIRD ANGLE PROJECTION	TOLERANCE UNLESS OTHERWISE SPECIFIED					
	DRAWN BY	APPV'D BY	DATE	SIZE	FSCM NO.	DRAWING NO.	
	L. WENGSTROM	J.K.	6/30/04	A	55335	BGF717-UV351	
	- CAD DRAWING -			SCALE	RELEASED DATE	REVISION DATE	REV. NO.
	MANUAL REVISIONS NOT PERMITTED			NONE	6/30/04		1 OF 1

REV. NO.	DESCRIPTION/ECO NUMBER	APPV'D DATE
	RELEASE & CANCEL P-0402-06	6/30/04