



JKL LAMP PART NUMBER	COLOR	STARTING CIRCUIT VOLTAGE VS (Vrms)	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mArms)	BRIGHTNESS (CANDELA/m ²)	*RATED LIFE (HRS)
CF24236-24B	WHITE 7,570°k x = .300 y = .308	1260 TYP. @ 0°C	516	5.0	32,000±10%	50,000
			501	6.5	38,000±10%	30,000

* RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

<p>THIRD ANGLE PROJECTION</p>			<p>METRIC</p> <p>DIMENSIONS ARE IN MILLIMETERS</p> <p>TOLERANCE UNLESS OTHERWISE SPECIFIED</p> <p>1 PL +/- 0.3</p> <p>2 PL +/- 0.2</p> <p>ANGLE +/- 0</p>		<p>JKL COMPONENTS CORPORATION</p>																
<p>DRAWN BY L. WENGSTROM</p>			<p>APPVD BY J.K.</p>		<p>DATE 1/20/04</p>		<p>SIZE A</p>		<p>FSCM NO. 55335</p>		<p>DRAWING NO. CF24236-24B</p>										
<p>RELEASED</p>			<p>1/20/04</p>		<p>APPVD DATE</p>		<p>- CAD DRAWING -</p> <p>MANUAL REVISIONS NOT PERMITTED</p>					<p>SCALE NONE</p>		<p>RELEASED DATE 1/20/04</p>		<p>REVISION DATE</p>		<p>REV. NO.</p>		<p>SHEET 1 OF 1</p>	