



JKL LAMP NUMBER	VOLTS RATED	AMPS ±10%	*MSCP ±25%	*LUMENS ±25%	AVERAGE LIFE HRS.	FILAMENT TYPE
SM0680N	6.0	.080	.159	2.00	2,000	C-2R
SM1250N	12.0	.050	.215	2.70	2,000	C-2V
SM1480N	14.0	.080	.502	6.31	1,000	C-2V
SM1860N	18.0	.060	.398	5.00	2,000	C-2V
SM2425N	24.0	.025	.215	2.70	2,000	C-2F
SM2840N	28.0	.040	.342	4.30	1,000	C-2F

				METRIC DIMENSIONS ARE IN MILLIMETERS TOLERANCE UNLESS OTHERWISE SPECIFIED 1 PL +/- 0.2 2 PL +/- 0 ANGLE +/- 0		JKL COMPONENTS CORPORATION			
		THIRD ANGLE PROJECTION		DRAWN BY L. WENGSTROM		APPV'D BY DATE QC 8/16/00		TITLE T-1 1/2 TELEPHONE SLIDE BASE PILOT T4.9	
RELEASED		8/16/00		SCALE NONE		FSCM NO. 55335		DRAWING NO. SLIDE BASE PILOT T4.9	
REV. NO.	DESCRIPTION/ECO NUMBER	APPV'D DATE	- CAD DRAWING - MANUAL REVISIONS NOT PERMITTED		SCALE NONE	RELEASED DATE 8/16/00	REVISION DATE	REV. NO.	SHEET 1 OF 1