

ALUMILINE® SLIM LED FIXTURE

Features

Long Life
Low Power Consumption
RoHS Compliant
No UV Emission
Thermally Optimized
Low Profile

Protected against Dust and Splashing Water
Mounting Holes for Ease of Installation
Available in Multiple LED Spacing
Cool, Neutral, Warm White Light Output
Custom Connectors Available
Low Voltage Operation

A DIM.	B DIM.	Power	Current	Lumen
± 1.2mm (±0.05 inch)	mm (inch)	(W)	(mA)	Flux (lm)
310 (12.20)	10 (.40)	2.0	85	150
610 (24.00)	10 (.40)	4.1	170	300
910 (35.83)	10 (.40)	6.1	255	450
1210 (47.64)	10 (.40)	8.2	340	600


310 (12.20)	16.7 (.66)	1.2	51	90
610 (24.00)	16.7 (.66)	2.4	102	180
910 (35.83)	16.7 (.66)	3.7	153	270
1210 (47.64)	16.7 (.66)	4.8	201	360

310 (12.20)	25 (.98)	0.8	34	60
610 (24.00)	25 (.98)	1.6	68	120
910 (35.83)	25 (.98)	2.4	102	180
1210 (47.64)	25 (.98)	3.3	136	240



Accessories

ZPS-2435 24V, 35 Watt Power Supply
ZPS-2460 24V, 60 Watt Power Supply
ZDM-01 PWM LED Dimmer
Note: ZPS-2435 and ZPS-2460 require use of wire nuts for connections.



Part Number Ordering Guide

ZLF - DIM. A	COLOR	OPTION	DIM. B	VOLTS
XXXX /	XX /	X /	XX -	XX
0310	W1 - 3500K	X	10 - 10mm	12
0610	W3 - 5300K		16 - 16.7mm	24
0910	W5 - 6000K		25 - 25mm	
1210	W6 - 7500K			

Notes

- Please contact JKL if you prefer this product supplied with a connector.
- Please refer to JKL Application Sheet: JKL-AS-ZLF-ALUMILINE-SLIM for Installation and Power Recommendations.

			METRIC		DIMENSIONS ARE MILLIMETER (INCH)		JKL COMPONENTS CORPORATION			
			THIRD ANGLE PROJECTION		TOLERANCE UNLESS OTHERWISE SPECIFIED		TITLE			
					1 PL +/- REF.		ALUMILINE® SLIM LED FIXTURE			
					2 PL +/- REF.					
					ANGLE +/- REF.					
B			DRAWN BY		APP'D BY		SIZE		FSCM NO.	
A			L. WENGSTROM		DATE		A		55335	
					L.R.				DRAWING NO.	
									ZLF-MULTI	