



# VGA and Touchscreen Interface for PC/104 MPC204



## Features

- ✓ Low-cost VGA, 8 and 16-bit versions
- ✓ Drives flat panel displays and CRTs
- ✓ Drives wide variety of panel types (320x200 to 1280x1024)
- ✓ Software-driven matrix touchscreen interface (up to 16 x 8)
- ✓  $V_{CC}$  and  $V_{EE}$  switching/sequencing
- ✓ Optional  $V_{EE}$  supply (0 to -22V)
- ✓ Optional AT keyboard port
- ✓ PC/104 format

The MPC204 is a low cost PC/104 operator interface solution. It allows flat panel LCD displays to be driven with standard PC code. The VGA subsystem supports monochrome and active matrix color. Standard VGA CRT monitors can also be driven. Panel and screen resolutions from 320x200 to 1280x1024 are supported.

An on-board VGA BIOS is in ROM. On-board switching of panel voltages, and an optional  $V_{EE}$  supply make panel interfacing easier. The MPC204 also includes an interface to

matrix touchscreens overlaid on a flat panel display. The VGA output can be used to draw pushbuttons and other controls on the flat panel display. The returned X and Y coordinates of a finger or stylus press can be used by application software to act on operator selections. If not used for a touchscreen, these lines provide 8 digital inputs and 16 digital outputs.

An optional IBM AT-compatible keyboard port is also available. The MPC204 can be programmed using standard PC languages.

### Software Support


*VGA BIOS included  
Touchscreen and KBD drivers  
included.*

### Compatible Hardware

*Any Micro/sys CPU with  
PC/104 expansion connector  
[See Section 1]  
LCD Panels Kits, FPKIT-xxx  
[Items above in Section 4]  
Flat panel displays  
VGA CRTs  
Matrix touchscreens  
AT keyboards*

### Mounting/Packaging

*PC/104 standard*



## Specifications:

### Mechanical:

- ❑ PC/104 standard, MPC204
- ❑ 3.55" (plus I/O region) x 3.775" x .6"

### Power Requirements and switching:

- ❑ +5V  $\pm$  5% at 100mA max
- ❑ +12V  $\pm$  5% at 76mA max (if 204OPT1 installed)
- ❑ On-board switches for panel  $V_{cc}$  and  $V_{ee}$

### Environmental:

- ❑ 0° - +70°C operating
- ❑ -25° - +85°C storage
- ❑ 5%-95% relative humidity, non-condensing

### PC/104 Interface:

- ❑ 8/16-bit PC/104 module
- ❑ Standard VGA mapping, 4 selectable port areas for touchscreen and AT KBD
- ❑ IRQ9 for VGA

### Video Interface:

- ❑ 11 panel data lines, shift clock, line clock, frame clock,  $V_{cc}$ , gnd. Typical panels:  
 LG Semicon: LP064V1 color  
 Sharp: LM64K103 mono

### Touchscreen:

- ❑ Resistive matrix type, up to 8 x 16

### AT Keyboard Port Option:

- ❑ AT keyboard controller plus beeper control

### External Connections:

- ❑ 40-pin header for flat panel display, pinout per Sharp LM64P101 monochrome panel
- ❑ 14-pin header for CRT monitor
- ❑ 26-pin header for touchscreen
- ❑ 10-pin header for KBD/beeper option
- ❑  $V_{ee}$  input if supply option not installed

## Ordering Information:

MPC204	VGA, touch interface, 16-bit
MPC204-1	VGA, touch, AT KBD, 16-bit
MPC204-8	VGA, touch interface, 8-bit
MPC204-9	VGA, touch, AT KBD, 8-bit
204OPT1	Adjustable $V_{ee}$ supply onboard
204OPT2	Additional 512K RAM

### Related Products:

FPKIT-M01	Monochrome Panel Kit
FPKIT-C02	Active Color Panel Kit
CA4029-X	Family of cables to LCD panels
CA4030	Cable to female DB15 for CRT
CA4054	Keyboard, Beeper breakout cable