







N=Number of contacts



P.C.B LAYOUT



SIGN	DATE	DESCRIPTION	APPROVER

THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!

Material

- Terminal body (Contact pin): Brass
- Wire guard: Stainless steel
- Surface of solder tail: Tin plated
- Insulator (housing): Thermoplastic (UL94V-0)

Electrical

- Voltage rating: 250VAC
- Current rating: 8A
- Wire range:
 - Solid wire(AWG): 12-28
 - Stranded wire(AWG): 12-28
- Wire strip length: 6-7mm
- Withstanding Voltage: 1.5KV
- Operating temperature: -30°C to +105°C
- Soldering temperature: 250°C±10°C/5 Sec
- Safety approval: us

RoHS Compliant

PART NUMBER:

OSTHMXX9080

No. of Poles
02: 2 Poles
:
12: 12 Poles

COLOR

0: Black
5: Green
6: Blue
8: Grey (Standard)



ON-SHORE TECHNOLOGY, INC.

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF ON-SHORE TECHNOLOGY, INC. AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF ON-SHORE TECHNOLOGY, INC.

TITLE		OSTHM 7.5mm Series Dip solder					
PART NO.	OSTHMXX9080			DWG NO.	OSTHMXX9080.DWG		
APPROVED	CHECKED	DESIGNED	DRAWN	CUST NO.			
Shi jun 2006.11.01	Marvin 2006.06.26	Marvin 2006.06.26	Marvin 2006.06.26				
				SHEET: 01/01			
				UNIT: mm		Tolerance	
				SCALE: NONE		X.	±0.50
				REV: D		X.X	±0.30
						X.XX	±0.10
						X°	±1°