







N=Number of poles



RECOMMENDED PCB LAYOUT



THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF ON-SHORE TECHNOLOGY, INC. AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF ON-SHORE TECHNOLOGY, INC.

SIGN	DATE	DESCRIPTION	APPROVER
		THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!	

Material

- Terminal body
- (metal housing): Brass(CuZn)
- Terminal screw: Steel Zinc plating "-" slot type
- Wire guard: Stainless steel
- Surface of solder tail: Tin plated
- Insulator (housing): Thermoplastic (UL94V-0)

Electrical

- Voltage rating: 300VAC
- Current rating: 15A
- Wire range:
 - Solid wire(AWG): 14-22
 - Stranded wire(AWG): 14-22
- Torque(Lb-In): 3.5
- Screw: M3
- Wire strip length: 6-7mm
- Withstanding Voltage: 1.5KV
- Operating temperature: -30°C to +105°C
- Soldering temperature: 250°C±10°C/5 Sec
- Safety Approval: 

RoHS Compliant

PART NUMBER:

OSTTAXX4163

No. of Poles
02 2 Poles
03 3 Poles
... ..
24 24 Poles

COLOR
0: Black
5: Green
6: Blue (Standard)
8: Grey



ON-SHORE TECHNOLOGY, INC.

TITLE		OSTTA - 5.08mm series one interlock, 4.0mm pin				
PART NO.	OSTTAXX4163			DWG NO.	OSTTAXX4163.DWG	
APPROVED	CHECKED	DESIGNED	DRAWN	CUST NO.		
	Marvin 2006.02.08	Marvin 2006.02.08	Marvin 2006.02.08		UNIT: mm	Tolerance
				SHEET: 01/01	SCALE: NONE	X. ±0.50
					REV: C	X.X ±0.30
						X.XX ±0.10
						X° ±1°